Printing date 03/14/2018 Reviewed on 06/28/2017

### 1 Identification

- · Product identifier
- · Trade name: 19133 Honda Atomic Blue B537M
- · Article number: 19133
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

  (Contd. on page 2)

USA



Printing date 03/14/2018

Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 1)

Reviewed on 06/28/2017

#### · Hazard pictograms









GHS04

GHS07

#### · Signal word Danger

### · Hazard-determining components of labeling:

acetone

toluene

*4-methylpentan-2-one* 

*n-butyl* acetate

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

P312 Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. P314 P337+P313 *If eye irritation persists: Get medical advice/attention.* 

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 4Reactivity = 3

(Contd. on page 3)

(Contd. of page 2)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

· HMIS-ratings (scale 0 - 4)

HEALTH 2 Health = 2FIRE 4 Fire = 4REACTIVITY 3 Reactivity = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description:

Mixture: consisting of the following components.

Weight percentages

0 1	n eight percentages		
· Dangerous	· Dangerous components:		
67-64-1	acetone	13-30%	
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%	
123-86-4	n-butyl acetate	10-13%	
108-65-6	2-methoxy-1-methylethyl acetate	10-13%	
110-19-0	isobutyl acetate	5-7%	
108-88-3	toluene	1.5-5%	
763-69-9	ethyl 3-ethoxypropionate	1.5-5%	
12001-26-2	Mica	1.5-5%	
108-10-1	4-methylpentan-2-one	1-1.5%	
100-41-4	ethylbenzene	≥0.1-≤1%	

## 4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 3)

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

67-64-1 acetone	200 ppm
123-86-4 n-butyl acetate	5 ppm
108-65-6 2-methoxy-1-methylethyl acetate	50 ppm
110-19-0 isobutyl acetate	450 ppm
108-88-3 toluene	67 ppm
763-69-9 ethyl 3-ethoxypropionate	1.6 ppm
12001-26-2 Mica	$9 \text{ mg/m}^3$
108-10-1 4-methylpentan-2-one	75 ppm
110-43-0 heptan-2-one	150 ppm
13463-67-7 titanium dioxide	30 mg/m
1330-20-7 xylene	130 ppm
100-41-4 ethylbenzene	33 ppm
71-36-3 butan-1-ol	60 ppm
1333-86-4 Carbon black	$9 \text{ mg/m}^3$
7727-43-7 barium sulphate, natural	15 mg/m
25322-68-3 Polyethylene glycol	30 mg/m
PAC-2:	
67-64-1 acetone	3200* ppm
123-86-4 n-butyl acetate	200 ppm
108-65-6 2-methoxy-1-methylethyl acetate	1,000 ppm
110-19-0 isobutyl acetate	1300* ppm
108-88-3 toluene	560 ppm
763-69-9 ethyl 3-ethoxypropionate	18 ppm
12001-26-2 Mica	99 mg/m³
108-10-1 4-methylpentan-2-one	500 ppm
110-43-0 heptan-2-one	670 ppm

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

13463-67-7 titanium dioxide	(Contd. of page $330 \text{ mg/m}^3$
1330-20-7 xylene	920* ppm
100-41-4 ethylbenzene	1100* ppm
71-36-3 butan-1-ol	800 ppm
1333-86-4 Carbon black	$99 \text{ mg/m}^3$
7727-43-7 barium sulphate, natural	170 mg/m³
25322-68-3 Polyethylene glycol	1,300 mg/m
PAC-3:	
67-64-1 acetone	5700* ppm
123-86-4 n-butyl acetate	3000* ppm
108-65-6 2-methoxy-1-methylethyl acetate	5000* ppm
110-19-0 isobutyl acetate	7500** ppn
108-88-3 toluene	3700* ppm
763-69-9 ethyl 3-ethoxypropionate	110 ppm
12001-26-2 Mica	590 mg/m³
108-10-1 4-methylpentan-2-one	3000* ppm
110-43-0 heptan-2-one	4000* ppm
13463-67-7 titanium dioxide	2,000 mg/m
1330-20-7 xylene	2500* ppm
100-41-4 ethylbenzene	1800* ppm
71-36-3 butan-1-ol	8000** ppn
1333-86-4 Carbon black	$590 \text{ mg/m}^3$
7727-43-7 barium sulphate, natural	990 mg/m³
25322-68-3 Polyethylene glycol	7,700 mg/m

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

IIS.



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 5)

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

PEL	Long-term value: 2400 mg/m³, 1000 ppm	
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm	
TLV	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI	
123-8	66-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Long-term value: 950 mg/m³, 200 ppm	
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm	
108-6.	5-6 2-methoxy-1-methylethyl acetate	
WEEL	L Long-term value: 50 ppm	
110-1	9-0 isobutyl acetate	
PEL	Long-term value: 700 mg/m³, 150 ppm	
REL	Long-term value: 700 mg/m³, 150 ppm	
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm	
108-8	88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 75 mg/m³, 20 ppm BEI	
12001	1-26-2 Mica	
PEL	Long-term value: 20 mppcf ppm <1% crystalline silica	
REL	Long-term value: 3* mg/m³ *respirable dust; containing < 1% quartz	
TLV	Long-term value: 3* mg/m³ *as respirable fraction	
108-1	0-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m³, 100 ppm	

USA

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

REL Short-term value: 300 mg/m², 75 ppm Long-term value: 207 mg/m², 50 ppm TLV Short-term value: 82 mg/m², 20 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m², 100 ppm REL Short-term value: 435 mg/m², 120 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m², 100 ppm TLV Long-term value: 437 mg/m², 120 ppm BEI 100-41-4 ethylbenzene PEL Short-term value: 437 mg/m², 120 ppm BEI 100-term value: 87 mg/m², 120 ppm BEI 100-term value: 87 mg/m², 120 ppm BEI 100-term value: 87 mg/m², 120 ppm BEI Short-term value: 87 mg/m², 120 ppm BEI O.2 mg/m², mg/m², 120 ppm BEI Short-term value: 88 mg/m², 120 ppm BEI Short-term value: 87 mg/m², 120 ppm BEI Short-term value: 88 mg/m², 120 ppm BEI Short-term value: 87 mg/		
Long-term value: 205 mg/m³, 50 ppm	DEL	(Contd. of page
TLV Short-term value: 307 mg/m², 75 ppm Long-term value: 82 mg/m², 20 ppm BEI  100-41-4 ethylbenzene  PEL Long-term value: 545 mg/m², 100 ppm REL Short-term value: 545 mg/m², 100 ppm Long-term value: 435 mg/m², 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI  Ingredients with biological limit values: 67-64-1 acetone  BEI So mg/L Medium: urine Time: end of shift Parameter: Actone (nonspecific)  108-88-3 toluene  BEI O.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: -C-cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one BEI I mg/L Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene BEI O.7 g/g creatinine Medium: urine Time: ond of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  Medium: end-exhaled air Time: not critical	REL	
Long-term value: 82 mg/m³, 20 ppm     BE    100-41-4 ethylbenzene     PEL   Long-term value: 435 mg/m³, 100 ppm     Short-term value: 435 mg/m³, 125 ppm     Long-term value: 435 mg/m³, 120 ppm     TLV   Long-term value: 87 mg/m³, 20 ppm     BE    Ingredients with biological limit values:     67-64-1 acetone     BE  50 mg/L     Medium: urine     Time: end of shift     Parameter: Acetone (nonspecific)     108-88-3 toluene     BE  0.2 mg/L     Medium: blood     Time: prior to last shift of workweek     Parameter: Toluene     0.03 mg/L     Medium: urine     Time: end of shift     Parameter: Toluene     0.3 mg/g creatinine     Medium: urine     Time: end of shift     Parameter: -Cresol with hydrolysis (background)     108-10-1 4-methylpentan-2-one     BE    mg/L     Medium: urine     Time: end of shift     Parameter: MBK     100-41-4 ethylbenzene     BE  0.7 e/g creatinine     Medium: urine     Time: end of shift at end of workweek     Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)     Medium: end-exhaled air     Time: not critical	<i>(</i> 11.17	
BET   100-41-4 ethylbenzene   PEL   Long-term value: 435 mg/m², 100 ppm   REL   Short-term value: 345 mg/m², 125 ppm   Long-term value: 435 mg/m², 100 ppm   Long-term value: 435 mg/m², 100 ppm   Long-term value: 87 mg/m², 20 ppm   BET   So mg/L   Long-term value: 87 mg/m², 20 ppm   BET   So mg/L   Medium: urine   Time: end of shift   Parameter: Acetone (nonspecific)   108-88-3 toluene   BET   0.02 mg/L   Medium: blood   Time: prior to last shift of workweek   Parameter: Toluene   0.03 mg/L   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: O-Cresol with hydrolysis (background)   108-10-1-4-methylpentan-2-one   BET   1 mg/L   Medium: urine   Time: end of shift   Parameter: MBK   100-41-4 ethylbenzene   BET   0.7 gig creatinine   Medium: urine   Time: end of shift   Parameter: MBK   100-41-4 ethylbenzene   BET   0.7 gig creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: end-exhaled air   Time: not critical	TLV	
100-41-4 ethylbenzene		
PEL   Long-term value: 435 mg/m³, 100 ppm   Short-term value: 345 mg/m³, 125 ppm   Long-term value: 437 mg/m³, 20 ppm   BEI   Ingredients with biological limit values:   Gr-64-1 acetone   BEI   50 mg/L   Medium: urine   Time: end of shift parameter: Acetone (nonspecific)   Holdium: blood   Time: prior to last shift of workweek   Parameter: Toluene   O.3 mg/L   Medium: urine   Time: end of shift parameter: Toluene   O.3 mg/L   Medium: urine   Time: end of shift parameter: Toluene   O.3 mg/c creatinine   Medium: urine   Time: end of shift parameter: Toluene   O.3 mg/c creatinine   Medium: urine   Time: end of shift parameter: o-Cresol with hydrolysis (background)   Host-Io-1 4-methylpentan-2-one   BEI   1 mg/L   Medium: urine   Time: end of shift parameter: MIBK   Hoo-41-4 ethylbenzene   Holdium: urine   Holdium:	100 41	
REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 87 mg/m³, 20 ppm BEI Jong-term value: 87 mg/m³, 20 ppm BEI 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)  108-88-3 toluene BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: -Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one BEI 1 mg/L Medium: urine Time: end of shift Parameter: MBK  100-41-4 ethylbenzene BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  Medium: end-exhaled air Time: not critical		
Long-term value: 435 mg/m³, 100 ppm		
TLV Long-term value: 87 mg/m³, 20 ppm BEI Ingredients with biological limit values:  67-64-1 acetone BEI 50 mg/L	REL	
Ingredients with biological limit values: 67-64-1 acetone  BEI   50 mg/L   Medium: urine   Time: end of shift   Parameter: Acetone (nonspecific)  108-88-3 toluene  BEI   0.02 mg/L   Medium: blood   Time: prior to last shift of workweek   Parameter: Toluene   0.03 mg/L   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: o-Cresol with hydrolysis (background)  108-10-14-methylpentan-2-one  BEI   mg/L   Medium: urine   Time: end of shift   Parameter: o-Cresol with hydrolysis (background)  108-10-14-methylpentan-2-one  BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift   Parameter: MIBK   Time: end of shift   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: end-exhaled air   Time: not critical		
Ingredients with biological limit values:  67-64-1 acetone  BEI 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)  108-88-3 toluene  BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: -Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI 1 mg/L Medium: urine Time: end of shift Parameter: MBK  100-41-4 ethylbenzene  BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  Medium: end-exhaled air Time: not critical	TLV	9 11
67-64-1 acetone  BEI   50 mg/L   Medium: urine   Time: end of shift   Parameter: Acetone (nonspecific)  108-88-3 toluene  BEI   0.02 mg/L   Medium: blood   Time: prior to last shift of workweek   Parameter: Toluene   0.03 mg/L   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: -Cresol with hydrolysis (background)  108-10-14-methylpentan-2-one   BEI   1 mg/L   Medium: urine   Time: end of shift   Parameter: MIBK   Parameter: MIBK   Parameter: Mist   Parameter: Mist   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: end-exhaled air   Time: not critical		
BEI   50 mg/L   Medium: urine   Time: end of shift   Parameter: Acetone (nonspecific)   108-88-3 toluene   BEI   0.02 mg/L   Medium: blood   Time: prior to last shift of workweek   Parameter: Toluene   0.03 mg/L   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: Ocresol with hydrolysis (background)   108-10-14-methylpentan-2-one   BEI   1 mg/L   Medium: urine   Time: end of shift   Parameter: MIBK   100-41-4 ethylbenzene   BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: end-exhaled air   Time: not critical   Time: not critic		-
Medium: urine Time: end of shift Parameter: Acetone (nonspecific)  108-88-3 toluene  BEI   0.02 mg/L   Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L   Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: -Cresol with hydrolysis (background)  108-10-14-methylpentan-2-one  BEI   1 mg/L   Medium: urine Time: end of shift Parameter: MBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  Medium: end-exhaled air Time: not critical		
Time: end of shift Parameter: Acetone (nonspecific)  108-88-3 toluene  BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   I mg/L Medium: urine Time: end of shift Parameter: MBK  100-41-4 ethylbenzene  BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  Medium: end-exhaled air Time: not critical		
Parameter: Acetone (nonspecific)     108-88-3 toluene     BEI   0.02 mg/L   Medium: blood     Time: prior to last shift of workweek     Parameter: Toluene     0.03 mg/L   Medium: urine     Time: end of shift     Parameter: Toluene     0.3 mg/g creatinine     Medium: urine     Time: end of shift     Parameter: o-Cresol with hydrolysis (background)     108-10-1 4-methylpentan-2-one     BEI   1 mg/L   Medium: urine     Time: end of shift     Parameter: MIBK     100-41-4 ethylbenzene     BEI   0.7 g/g creatinine     Medium: urine     Time: end of shift at end of workweek     Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)     Medium: end-exhaled air     Time: not critical		
108-88-3 toluene  BEI   0.02 mg/L   Medium: blood   Time: prior to last shift of workweek   Parameter: Toluene   0.03 mg/L   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: o-Cresol with hydrolysis (background)   108-10-1 4-methylpentan-2-one   BEI   1 mg/L   Medium: urine   Time: end of shift   Parameter: MIBK   100-41-4 ethylbenzene   BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: end-exhaled air   Time: not critical		
BEI   0.02 mg/L   Medium: blood   Time: prior to last shift of workweek   Parameter: Toluene   0.03 mg/L   Medium: urine   Time: end of shift   Parameter: Toluene   0.3 mg/g creatinine   Medium: urine   Time: end of shift   Parameter: O-Cresol with hydrolysis (background)   108-10-1 4-methylpentan-2-one   BEI   I mg/L   Medium: urine   Time: end of shift   Parameter: MIBK   100-41-4 ethylbenzene   107 g/g creatinine   Medium: urine   Time: end of shift   Parameter: MIBK   100-41-4 ethylbenzene   Medium: urine   Time: end of shift   Time: ond of shift   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   Medium: end-exhaled air   Time: not critical   Time: not critical		· · · · · · · · · · · · · · · · · · ·
Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   1 mg/L Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   1 mg/L Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
Parameter: Toluene  0.03 mg/L  Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   mg/L   Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI I mg/L Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)		
Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   1 mg/L Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical	1 '	arameter. 10tache
Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   1 mg/L Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical	0.	$0.03~\mathrm{mg/L}$
Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   mg/L   Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   1 mg/L   Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine   Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical	Ti	ime: end of shift
Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   I mg/L   Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine   Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical	P	Parameter: Toluene
Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   I mg/L   Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine   Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
Time: end of shift Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   I mg/L   Medium: urine   Time: end of shift   Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air   Time: not critical		
Parameter: o-Cresol with hydrolysis (background)  108-10-1 4-methylpentan-2-one  BEI   I mg/L   Medium: urine   Time: end of shift   Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   - Medium: end-exhaled air   Time: not critical		
108-10-1 4-methylpentan-2-one  BEI   I mg/L   Medium: urine   Time: end of shift   Parameter: MIBK  100-41-4 ethylbenzene  BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)   - Medium: end-exhaled air   Time: not critical		
BEI   1 mg/L   Medium: urine   Time: end of shift   Parameter: MIBK    100-41-4 ethylbenzene    BEI   0.7 g/g creatinine   Medium: urine   Time: end of shift at end of workweek   Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)    - Medium: end-exhaled air   Time: not critical		
Medium: urine Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		**
Time: end of shift Parameter: MIBK  100-41-4 ethylbenzene  BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
Parameter: MIBK  100-41-4 ethylbenzene  BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical	100-41	1-4 ethylbenzene
Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical	BEI 0.	2.7 g/g creatinine
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical		
- Medium: end-exhaled air Time: not critical		
Time: not critical	Pc	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
Time: not critical		
Time: not critical	M	Medium: end-exhaled air
Parameter: Ethyl henzene (semi-augntitative)		
т ининстет. Бинут бенгене (зени-чийнийнуе)	$P^{c}$	Parameter: Ethyl benzene (semi-quantitative)

· Additional information: The lists that were valid during the creation were used as basis.

 $(Contd.\ on\ page\ 8)$ 



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 7)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:

Safety glasses



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Color: Dark blue
Odor: Characteristic
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55.8-56.6 °C

(Contd. on page 9)

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

	(Contd. of page
Flash point:	-103 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture. Avoid high heat
Explosion limits:	
Lower:	1.9 Vol %
Upper:	13 Vol %
Vapor pressure at 20 °C:	233 hPa
Density at 20 °C:	$0.75922 \text{ g/cm}^3$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	91.5 %
VOC content:	61.65 %
	656.3 g/l / 5.48 lb/gl
Solids content:	8.4 %
Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Nitrogen oxides

Hydrocarbons

Carbon monoxide and carbon dioxide

HSA

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 9)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· L	· LD/LC50 values that are relevant for classification:			
10	108-88-3 toluene			
0	ral	LD50	5,000 mg/kg (rat)	
D	ermal	LD50	12,124 mg/kg (rabbit)	
In	ıhalative	LC50/4 h	5,320 mg/l (mouse)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	nternational Agency for Research on Cancer)	
108-88-3	toluene	3
108-10-1	4-methylpentan-2-one	2B
13463-67-7	titanium dioxide	2B
1330-20-7		3
	ethylbenzene	2B
1333-86-4	Carbon black	2B

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 11)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

· Other adverse effects No further relevant information available.

(Contd. of page 10)

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1950
UN proper shipping name	
DOT	Aerosols, flammable
ADR IMDG	1950 Aerosols AEROSOLS
IATA	AEROSOLS AEROSOLS, flammable
Transport hazard class(es)	
DOT	
Lunion at set	
Class	2.1
Label	2.1
ADR	
Class	2 5F Gases
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void

USA -

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

	(Contd. of page 1
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Gases
EMS Number:	$F ext{-}D,S ext{-}\check{U}$
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear of living
	quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class 1 except fo
	division 1.4. For AEROSOLS with a capacity above 1 litre
	Segregation as for the appropriate subdivision of class 2. Fo
	WASTE AEROSOLS: Segregation as for the appropriate subdivisio
	of class 2.
Towns of the House of the Assessment	v
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.
	ної аррисаоте.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
· ADR	
Excepted quantities (EQ)	Code: E0
1 1 ( <del>2</del> /	Not permitted as Excepted Quantity
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

None of the	e ingredient is listed.
Section 31.	3 (Specific toxic chemical listings):
108-88-3	toluene
	Acrylic Resin
108-10-1	4-methylpentan-2-one
1330-20-7	xylene
100-41-4	ethylbenzene
71-36-3	butan-1-ol
7727-43-7	barium sulphate, natural
	(Contd. on pag

USA


SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

nces Control Act):
ices Control Act):
acetate
oxy-1-methylethyl acetate
acetate
aceiuie
ethoxypropionate
se Acetate Butyrate
Plpentan-2-one
2-one
ı dioxide
3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
cyanine Blue
nzene
-ol
black
2,6,6-Pentamethyl-4-piperidinyl) sebacate
y-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxypheny opyl]-ω-hydroxy-
y-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]- $\omega$ -(2)- $\omega$ -(2)- $\omega$ -(2)- $\omega$ -(2)- $\omega$ -(2)- $\omega$ -(2)- $\omega$ -(3)-(3)-(4)-(4)-(4)-(5)-(5)-(6)-(6)-(6)-(6)-(6)-(6)-(6)-(6)-(6)-(6
sulphate, natural
(1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
ylene glycol
vl sebacate(Impurity)
idinol, 1,2,2,6,6 pentamethyl- (Impurity)
ury Act) (Substances not listed)
n gases, liquefied, sweetened
cause cancer:
pentan-2-one
dioxide
zene
olack
cause reproductive toxicity for females:
ts is listed.
cause reproductive toxicity for males:
cai ts i

(Contd. on page 14)



Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 13) · Chemicals known to cause developmental toxicity: 108-88-3 toluene 108-10-1 4-methylpentan-2-one · Cancerogenity categories · EPA (Environmental Protection Agency) 67-64-1 acetone 108-88-3 toluene II108-10-1 4-methylpentan-2-one 1330-20-7 xylene 100-41-4 ethylbenzene D 71-36-3 butan-1-ol 7727-43-7 barium sulphate, natural D, CBD(inh), NL(oral) TLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone A4108-88-3 toluene A413463-67-7 titanium dioxide A41330-20-7 xylene A4100-41-4 ethylbenzene A31333-86-4 Carbon black A4· NIOSH-Ca (National Institute for Occupational Safety and Health) 13463-67-7 titanium dioxide 1333-86-4 Carbon black

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07

- · Signal word Danger
- Hazard-determining components of labeling:

acetone

toluene

4-methylpentan-2-one

n-butyl acetate

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201

Obtain special instructions before use.

(Contd. on page 15)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

	(Contd. of page 14)
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety	assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- Date of preparation / last revision 03/14/2018 / 17
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols - Category 1

(Contd. on page 16)

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 19133 Honda Atomic Blue B537M

(Contd. of page 15)

Press. Gas: Gases under pressure – Compressed gas Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* Data compared to the previous version altered.