SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

1 Identification

- · Product identifier
- · Trade name: 46644, 46646 Rock-It XC Catalyst
- · Article number: 46644, 46646
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT SE 2 H371 May cause damage to organs.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

HDI Prepolymer

hexamethylene-di-isocyanate

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

(Contd. of page 1)

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H371 May cause damage to organs.

#### · Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

*P264 Wash thoroughly after handling.* 

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

*P330* Rinse mouth.

*P302+P352 If on skin: Wash with plenty of water.* 

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a poison center/doctor.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

*P321* Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

*P363* Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*2 Fire = 1Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

(Contd. on page 3)

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

		Contd. of page 2)
· Dangerous	components:	
28182-81-2	HDI Prepolymer	70-100%
822-06-0	hexamethylene-di-isocyanate	≥0.1-<0.5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

110100000000000000000000000000000000000	iner our for croemineurs	
· PAC-1:		
28182-81-2 HDI Pr	epolymer	7.8 mg/m³
822-06-0 hexame	thylene-di-isocyanate	0.018 ppm
· PAC-2:		
28182-81-2 HDI Pr	epolymer	86 mg/m³
		(Contd. on page 4)

USA

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

822-06-0	hexamethylene-di-isocyanate	(Contd. of page 3) 0.2 ppm
· PAC-3:		
28182-81-2	HDI Prepolymer	510 mg/m <sup>3</sup>
822-06-0	hexamethylene-di-isocyanate	3 ррт

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot$  *Specific end use(s) No further relevant information available.*

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

822-	822-06-0 hexamethylene-di-isocyanate	
REL	Long-term value: 0.035 mg/m³, 0.005 ppm	
	Ceiling limit value: 0.14* mg/m³, 0.02* ppm	
	*10-min	
TLV	Long-term value: $0.034 \text{ mg/m}^3$ , $0.005 \text{ ppm}$ BEI	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

ODI	. 7	7 7		
U Phy	cical an	dchor	mical n	roperties
	sicui un	u chen	micui p	Uperties

· Information on basic ph	ysical and chemical properties	
· General Information		
· Appearance:		
Form:	Liquid	
Color:	Yellow	
0.1		

· Odor threshold:	Not determined.	
· pH-value:	Not determined.	

· Change in condition	
Change in condition	

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	166 °C

· Flammability (solid, gaseous):	Not applicable.

· Decomposition temperature:	Not determined.

· Danger of explosion:	Product does not present an explosion nazara.
	In use, may form flammable/explosive vapour-air mixture.

. ,	Explosion	limits:	
	Lower		

Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C ·	1 1399 g/cm³

Density at 20°C.	1.1377 g/cm
· Relative density	Not determined.
· Vanor density	Not determined

(Contd. on page 6)

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

		(Contd. of page 5
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with	i	
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gl	
Solids content:	99.9 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· I.D/I.C50	values that are	relevant for	classification.

#### 28182-81-2 HDI Prepolymer

Oral	LD50	1,000 mg/kg (rat)
	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	137-1,150 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

(Contd. on page 7)

-USA

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

(Contd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 4 7			
14	Transport	าทา	rmation

· UN-Number · DOT, ADR, ADN, IATA · IMDG	Void UN3082
· UN proper shipping name · DOT, ADR, ADN, IATA · IMDG	Void ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HDI Prepolymer)

(Contd. on page 8)

USA ·

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

(Contd. of page 7) · Transport hazard class(es) · DOT, ADR, ADN, IATA Void · Class  $\cdot$  IMDG 9 Miscellaneous dangerous substances and articles · Class · Label · Packing group · DOT, ADR, IATA Void · IMDG III· Environmental hazards: Product contains environmentally hazardous substances: HDI Prepolymer · Marine pollutant: Yes Symbol (fish and tree) · Special precautions for user Not applicable. · EMS Number: F-A,S-F· Stowage Category  $\boldsymbol{A}$ · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot DOT$ · Remarks ORM-D 49CFR 173-150,156,306 · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Void · UN "Model Regulation":

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

822-06-0 hexamethylene-di-isocyanate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 9)

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

(Contd. of page 8)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

HDI Prepolymer

hexamethylene-di-isocyanate

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H371 May cause damage to organs.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection. [In case of inadequate ventilation] wear respiratory protection. P284 P301+P312 *If swallowed: Call a poison center/doctor if you feel unwell.* 

Rinse mouth. P330

P302+P352 If on skin: Wash with plenty of water.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for P304+P341

breathing.

(Contd. on page 10)

SEM

Printing date 04/19/2018 Version number 1 Reviewed on 04/19/2018

Trade name: 46644, 46646 Rock-It XC Catalyst

(Contd. of page 9)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a poison center/doctor.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

*P363* Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 04/19/2018 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 2: Specific target organ toxicity (single exposure) - Category 2

\* Data compared to the previous version altered.