



XXX UNIVERSAL SURFACE CLEANER

TECHNICAL DATA SHEET



Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

XXX Universal Surface Cleaner is a super compliant, waterborne cleaner that removes solvent and water soluble contaminants prior to refinishing.

FEATURES

- Best in class super compliant waterborne cleaner
- 2-in-1 cleaner reduces products needed in collision center
- Helps eliminate static for improved metallic orientation and reduced dust contamination
- Solvent strong in waterborne formula
- Exceptional grease-cutting power
- Multifunctional for primed or painted surfaces, leather, vinyl, plastic, aluminum, and bare metal

SUITABLE SUBSTRATES

- Primed or painted surfaces
- Leather
- Vinyl
- Plastic
- Aluminum
- Bare steel – limit exposure

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
77771	XXX Universal Surface Cleaner	Clear	Gallon
77774	XXX Universal Surface Cleaner	Clear	Quart
VOC Actual:			0.00 #/gal (0.00 g/L)
VOC Regulatory:			0.00 #/gal (0.00 g/L)

HANDLING AND APPLICATION



MIXING:

Ready to use.



APPLICATION:

Apply **XXX Universal Surface Cleaner** directly to surface or clean cloth. Apply enough material to adequately float contaminants out of sand scratches. Wipe dry in one direction with a clean, lint-free cloth, turning and changing cloths often.



Check local VOC regulations to ensure compliance of all products in your area.

If **XXX Universal Surface Cleaner** air dries on the surface, re-wet and dry completely with a clean, lint-free cloth.

Note: Use only with undyed, lint-free cloth. Be careful not to over saturate any exposed fiberglass. Do not use over body filler. Avoid prolonged contact with bare metal.



STORAGE:

XXX Universal Surface Cleaner should be stored in a cool, dry place with adequate ventilation away from heat, sparks, and flames. Protect from freezing. The shelf life for **XXX Universal Surface Cleaner** is 5 years when stored under normal conditions.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services, and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.