

## 1 Identification

- **Product identifier**
- **Trade name:** 39131;39134 Flexible Primer Surface
- **Article number:** 39131, 39134
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371 May cause damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)

toluene

n-butyl acetate

butanone

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)



Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

14808-60-7	Quartz (SiO <sub>2</sub> )	30-40%
1330-20-7	xylene	13-30%
108-88-3	toluene	10-13%
123-86-4	n-butyl acetate	≥7-<10%
78-93-3	butanone	1.5-5%
67-64-1	acetone	1.5-5%
14807-96-6	Talc	1-1.5%

**4 First-aid measures**

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
108-88-3	toluene	67 ppm
123-86-4	n-butyl acetate	5 ppm
78-93-3	butanone	200 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
67-64-1	acetone	200 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	60 ppm
100-41-4	ethylbenzene	33 ppm
67-56-1	methanol	530 ppm
78-83-1	butanol	150 ppm
57-55-6	Methyl glycol	30 mg/m <sup>3</sup>

· **PAC-2:**

14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm
108-88-3	toluene	560 ppm
123-86-4	n-butyl acetate	200 ppm
78-93-3	butanone	2700* ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
67-64-1	acetone	3200* ppm
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	120 ppm
100-41-4	ethylbenzene	1100* ppm
67-56-1	methanol	2,100 ppm
78-83-1	butanol	1,300 ppm

(Contd. on page 5)



Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 4)

57-55-6	Methyl glycol	1,300 mg/m <sup>3</sup>
<b>· PAC-3:</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
108-88-3	toluene	3700* ppm
123-86-4	n-butyl acetate	3000* ppm
78-93-3	butanone	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
67-64-1	acetone	5700* ppm
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	700 ppm
100-41-4	ethylbenzene	1800* ppm
67-56-1	methanol	7200* ppm
78-83-1	butanol	8000* ppm
57-55-6	Methyl glycol	7,900 mg/m <sup>3</sup>

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

14808-60-7 Quartz (SiO <sub>2</sub> )	
PEL	see Quartz listing

(Contd. on page 6)



**Trade name: 39131;39134 Flexible Primer Surface**

(Contd. of page 5)

REL Long-term value: 0.05\* mg/m<sup>3</sup>  
\*respirable dust; See Pocket Guide App. A  
TLV Long-term value: 0.025\* mg/m<sup>3</sup>  
\*as respirable fraction

**1330-20-7 xylene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI

**108-88-3 toluene**

PEL Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shift  
REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
BEI

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm  
REL Long-term value: 950 mg/m<sup>3</sup>, 200 ppm  
TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

**78-93-3 butanone**

PEL Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
REL Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
TLV Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
BEI

**67-64-1 acetone**

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 594 mg/m<sup>3</sup>, 250 ppm  
BEI

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

(Contd. on page 7)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 6)

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

**78-93-3 butanone**

BEI 2 mg/L  
Medium: urine  
Time: end of shift  
Parameter: MEK

**67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 7)

- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

#### · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	110 °C

· **Flash point:** 7 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

#### · Explosion limits:

Lower:	1.1 Vol %
Upper:	7 Vol %

· **Vapor pressure at 20 °C:** 29 hPa

· <b>Density at 20 °C:</b>	1.17935 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.

#### · Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

#### · Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:** 574.3 g/l / 4.79 lb/gal

(Contd. on page 9)





Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 8)

· <b>Organic solvents:</b>	51.1 %
· <b>Water:</b>	0.0 %
· <b>VOC content:</b>	48.07 %
	593.3 g/l / 4.95 lb/gl
· <b>Solids content:</b>	48.9 %
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

**108-88-3 toluene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO <sub>2</sub> )	1
1330-20-7	xylene	3
108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
14807-96-6	Talc	3
1333-86-4	Carbon black	2B

(Contd. on page 10)



Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 9)

111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
68911-87-5	montmorilontie clay complex	

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, ADR, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Paint
· <b>ADR</b>	1263 Paint, special provision 640D
· <b>IMDG, IATA</b>	PAINT

(Contd. on page 11)



Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids  
· **Label** 3

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**  
· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L  
· **Remarks** ORM-D 49CFR 173-150,156,306

· **ADR**  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **IMDG**  
· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

USA

(Contd. on page 12)



Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 11)

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
	Acrylic Resin
108-88-3	toluene
78-93-3	butanone
14807-96-6	Talc
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
67-56-1	methanol

· **TSCA (Toxic Substances Control Act):**

14808-60-7	Quartz (SiO <sub>2</sub> )
1330-20-7	xylene
108-88-3	toluene
123-86-4	n-butyl acetate
78-93-3	butanone
13463-67-7	titanium dioxide
67-64-1	acetone
14807-96-6	Talc
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
68911-87-5	montmorilontie clay complex
51274-00-1	YELLOW IRON OXIDE
1333-86-4	Carbon black
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
61791-55-7	Amines, N-tallow alkyltrimethylenedi-
67-56-1	methanol
78-83-1	butanol
57-55-6	Methyl glycol
7732-18-5	water

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO <sub>2</sub> )
1330-20-7	xylene
13463-67-7	titanium dioxide
1333-86-4	Carbon black
100-41-4	ethylbenzene

(Contd. on page 13)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 12)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

67-56-1 methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

108-88-3 toluene

II

78-93-3 butanone

I

67-64-1 acetone

I

111-76-2 2-butoxyethanol

NL

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

14808-60-7 Quartz (SiO<sub>2</sub>)

A2

1330-20-7 xylene

A4

108-88-3 toluene

A4

13463-67-7 titanium dioxide

A4

67-64-1 acetone

A4

14807-96-6 Talc

A4

1333-86-4 Carbon black

A4

111-76-2 2-butoxyethanol

A3

100-41-4 ethylbenzene

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7 Quartz (SiO<sub>2</sub>)

13463-67-7 titanium dioxide

1333-86-4 Carbon black

67-56-1 methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)

toluene

n-butyl acetate

butanone

(Contd. on page 14)



**Trade name: 39131;39134 Flexible Primer Surface**

(Contd. of page 13)

**· Hazard statements**

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H350 May cause cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H371 May cause damage to organs.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P321 Specific treatment (see on this label).
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· National regulations:**

**· Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

**· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** Environment protection department.

**· Contact:** Rita Joiner (rjoiner@semproducts.com)

(Contd. on page 15)



Printing date 03/14/2018

Reviewed on 06/20/2017

**Trade name: 39131;39134 Flexible Primer Surface**

(Contd. of page 14)

· **Date of preparation / last revision** 03/14/2018 / 5

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*ELINCS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Carc. 1A: Carcinogenicity – Category 1A*

*Repr. 2: Reproductive toxicity – Category 2*

*STOT SE 2: Specific target organ toxicity (single exposure) – Category 2*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

· **\* Data compared to the previous version altered.**

USA