

1 Identification

- **Product identifier**
- **Trade name:** *A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)*
- **Article number:** *A16015, A16018, A16508, A16515, A16518, A16525, A16528, A16535, A16538, A16545, A16548, A16565, A16568, A16578, A16585, A16588, A16595, A16598, A16705, A16708, A16715, A16718, A16726, A16728, A16815, A16825, A16855, A16875, A16879, A16885, A16905, A16910, A16915, A16920, A16950, A16960, A16970, API0246, API0248*
- **Application of the substance / the mixture** *Coating*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225*
- **Information department:**
*custcare@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone
1-800-831-1122, M - TH 7am - 4pm EDT*
- **Emergency telephone number:** *CHEMTREC 1-800-424-9300*

2 Hazard(s) identification

- **Classification of the substance or mixture**



*Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.*

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS07

- **Signal word** *Warning*
- **Hazard-determining components of labeling:**
*URETHANE POLYMER
Tetraethylene Glycol Di 2-ethylhexoate
Propylene glycol
dipropylene glycol butyl ether*
- **Hazard statements**
*H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.*
- **Precautionary statements**
*P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.*

(Contd. on page 2)

Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection / face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

	URETHANE POLYMER	13-30%
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate	1.5-5%
107-98-2	1-methoxy-2-propanol	1.5-5%
57-55-6	Propylene glycol	1-1.5%
29911-28-2	dipropylene glycol butyl ether	1-1.5%

4 First-aid measures

· **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 2)

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

107-98-2	1-methoxy-2-propanol	100 ppm
57-55-6	Propylene glycol	30 mg/m ³
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
124-68-5	2-amino-2-methylpropanol	17 mg/m ³

· PAC-2:

107-98-2	1-methoxy-2-propanol	160 ppm
57-55-6	Propylene glycol	1,300 mg/m ³
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m ³
1333-86-4	Carbon black	99 mg/m ³
124-68-5	2-amino-2-methylpropanol	190 mg/m ³

· PAC-3:

107-98-2	1-methoxy-2-propanol	660 ppm
----------	----------------------	---------

(Contd. on page 4)



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

		(Contd. of page 3)
57-55-6	Propylene glycol	7,900 mg/m ³
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m ³
1333-86-4	Carbon black	590 mg/m ³
124-68-5	2-amino-2-methylpropanol	570 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

107-98-2 1-methoxy-2-propanol

REL	Short-term value: 540 mg/m ³ , 150 ppm Long-term value: 360 mg/m ³ , 100 ppm
TLV	Short-term value: 369 mg/m ³ , 100 ppm Long-term value: 184 mg/m ³ , 50 ppm

57-55-6 Propylene glycol

WEEL	Long-term value: 10 mg/m ³
------	---------------------------------------

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 4)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties**· Information on basic physical and chemical properties****· General Information****· Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.**· Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C

· Flash point: 96 °C**· Flammability (solid, gaseous):** Not applicable.**· Ignition temperature:** 270 °C**· Decomposition temperature:** Not determined.**· Auto igniting:** Product is not selfigniting.**· Danger of explosion:** Product does not present an explosion hazard.
In use, may form flammable/explosive vapour-air mixture.**· Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

(Contd. on page 6)



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 5)

· Vapor pressure at 20 °C:	23 hPa
· Density at 20 °C:	1.02235 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	4.9 %
Water:	48.8 %
VOC content:	4.87 %
	99.2 g/l / 0.83 lb/gal
Solids content:	41.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

* 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)	
1333-86-4	Carbon black
	2B

(Contd. on page 7)

USA



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 6)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, ADN, IMDG, IATA** Void

· **UN proper shipping name**

· **DOT, ADR, ADN, IMDG, IATA** Void

· **Transport hazard class(es)**

· **DOT, ADR, ADN, IMDG, IATA**

· **Class** Void

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

(Contd. on page 8)



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 7)

· **Special precautions for user** Not applicable.· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.· **UN "Model Regulation":** Void

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

Acrylic Resin

143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol

· **TSCA (Toxic Substances Control Act):**

18268-70-7 Tetraethylene Glycol Di 2-ethylhexoate

107-98-2 1-methoxy-2-propanol

57-55-6 Propylene glycol

29911-28-2 dipropylene glycol butyl ether

1333-86-4 Carbon black

51200-87-4 4,4-dimethyl-1,3-oxizalidine

53320-86-8 CLAY

143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol

8042-47-5 White mineral oil, petroleum

124-68-5 2-amino-2-methylpropanol

7732-18-5 water

· **TSCA new (21st Century Act) (Substances not listed)**

URETHANE POLYMER

· **Proposition 65**· **Chemicals known to cause cancer:**

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

(Contd. on page 9)

Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 8)

· **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4	Carbon black	A4
-----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

URETHANE POLYMER
Tetraethylene Glycol Di 2-ethylhexoate
Propylene glycol
dipropylene glycol butyl ether

· **Hazard statements**

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a poison center/doctor if you feel unwell.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner (rjoiner@semproducts.com)

· **Date of preparation / last revision** 11/15/2022

(Contd. on page 10)



Trade name: A16015-A16970 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 9)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.