

Issuing Date 04-Nov-2013

Revision Date 24-May-2015

Revision Number 1

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**GHS product identifier**

Product Name Mothers NuLens Headlight Renewal Kit

**Other means of identification**

Product Code(s) 07251, 37251

Synonyms None

**Other Information**

This product is a kit and contains Mothers PowerPlastic 4Lights.

**Recommended use of the chemical and restrictions on use**

Recommended Use Headlight and Taillight Lens

Uses advised against No information available

**Supplier's details**

**Supplier Address**

MOTHERS POLISHES WAXES CLEANERS  
5456 Industrial Drive  
Huntington Beach, CA 92649  
TEL: 714-891-3364  
FAX: 714-893-1827

**Emergency telephone number**

Emergency Telephone Number Chemtrec Phone: 1-800-424-9300 (within the U.S.) or +1 703-527-3887 (outside the U.S.)

**2. HAZARDS IDENTIFICATION**

**Classification**

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Skin Sensitization	Category 1
--------------------	------------

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal Word</b> <b>Hazard Statements</b> • May cause an allergic skin reaction	<b>Warning</b>
---	----------------

**Appearance** White.**Physical State** Liquid.**Odor** Perfume**Precautionary Statements****Prevention**

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective gloves.

**General Advice**

- Specific treatment (see supplemental instructions on the administration of antidotes on this label)

**Skin**

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.

**Storage**

- None

**Disposal**

- Dispose of contents/container to an approved waste disposal plant.

**Hazard Not Otherwise Classified (HNOC)**

Not applicable

**Other information**

Prolonged or repeated contact may dry skin and cause irritation  
Harmful to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Deodorized kerosene	8008-20-6	10-25	*
Calcined kaolin clay	66402-68-4	7-13	*
Isopropyl alcohol	67-63-0	5-10	*
Siloxanes and Silicones, dimethyl, [[[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxy] -terminated	71750-80-6	1-5	*
Mineral Spirits	8052-41-3	1-5	*
D-Limonene	5989-27-5	<1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of necessary first-aid measures****General Advice**

May produce an allergic reaction. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a physician.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.
<b>Ingestion</b>	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician.
<b>Protection of First-aiders</b>	Use personal protective equipment.

**Most important symptoms/effects, acute and delayed****Most Important Symptoms/Effects** May cause allergic skin reaction.**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**Carbon dioxide (CO<sub>2</sub>). Foam. Dry powder. Dry chemical.**Unsuitable Extinguishing Media** No information available.**Specific Hazards Arising from the Chemical**

May cause sensitization by skin contact. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

**Explosion Data****Sensitivity to Mechanical Impact**

None.

**Sensitivity to Static Discharge**

None.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****Personal Precautions** Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.**Environmental Precautions****Environmental Precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.**Methods and materials for containment and cleaning up****Methods for Containment** Prevent further leakage or spillage if safe to do so.**Methods for Cleaning Up** Soak up with inert absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Ensure adequate ventilation.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

**Incompatible Products** Acids. Strong oxidizing agents. Chlorinated compounds.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Deodorized kerosene 8008-20-6	TWA: 200 mg/m <sup>3</sup> total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S*	-	TWA: 100 mg/m <sup>3</sup>
Calcined kaolin clay 66402-68-4	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr TWA: 0.2 mg/m <sup>3</sup> Mn	TWA: 5 mg/m <sup>3</sup> Zr (vacated) TWA: 5 mg/m <sup>3</sup> Zr (vacated) STEL: 10 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup> (vacated)	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m <sup>3</sup> TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Mineral Spirits 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup> (vacated)	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Pseudocumene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 325 mg/m <sup>3</sup> STEL: 250 ppm
Diethanolamine 111-42-2	TWA: 1 mg/m <sup>3</sup> inhalable fraction and vapor S*	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m <sup>3</sup>	TWA: 3 ppm TWA: 15 mg/m <sup>3</sup>
Cupric nitrate 3251-23-8	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-	IDLH: 100 mg/m <sup>3</sup> Cu dust and mist TWA: 1 mg/m <sup>3</sup> Cu dust and mist

*Immediately Dangerous to Life or Health.*

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Safety glasses with side-shields.
<b>Skin and Body Protection</b>	Wear protective gloves/clothing.
<b>Respiratory Protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Liquid.	<b>Appearance</b>	White.
<b>Odor</b>	Perfume.	<b>Odor Threshold</b>	No information available.
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks/ - Method</u></b>	
pH	9.0	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	93.3 °C	None known	
Flash Point	> 105 °C / > 221 °F	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	No data available	None known	
Vapor Density	No data available	None known	
Specific Gravity	1.008	None known	
Water Solubility	No data available	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature	No data available	None known	
Viscosity	600-900 cps	None known	
<b>Flammable Properties</b>	Not flammable		
<b>Explosive Properties</b>	No data available		
<b>Oxidizing Properties</b>	No data available		
<b><u>Other information</u></b>			
<b>VOC Content (%)</b>	No data available		

## 10. STABILITY AND REACTIVITY

### **Reactivity**

No data available.

### **Chemical stability**

Stable under recommended storage conditions.

### **Possibility of hazardous reactions**

None under normal processing.

### **Hazardous Polymerization**

Hazardous polymerization does not occur.

### **Conditions to avoid**

Do not freeze. Heat, flames and sparks.

### **Incompatible materials**

Acids. Strong oxidizing agents. Chlorinated compounds.

### **Hazardous decomposition products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## **11. TOXICOLOGICAL INFORMATION**

### **Information on likely routes of exposure**

#### **Product Information**

<b>Inhalation</b>	Avoid breathing vapors or mists. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye Contact</b>	Contact with eyes may cause irritation.
<b>Skin Contact</b>	May cause sensitization of susceptible persons. Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### **Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Deodorized kerosene	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Isopropyl alcohol	= 4396 mg/kg ( Rat )	12800 mg/kg ( Rat ) 12870 mg/kg ( Rabbit )	72.6 mg/L ( Rat ) 4 h
Mineral Spirits	-	-	-
D-Limonene	5000 mg/kg ( Rat )	>5000 mg/kg ( Rabbit )	-

### **Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Allergic skin reactions or irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

### **Delayed and immediate effects and also chronic effects from short and long term exposure**

**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenic Effects** No information available.  
**Carcinogenicity** Occupational health effects due to inhalation of mineral dusts incorporating crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc) graphite or coal unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Deodorized kerosene	A3	Group 3		
Calcined kaolin clay				X
Isopropyl alcohol		Group 3		
D-Limonene		Group 3	-	-

**ACGIH: (American Conference of Governmental Industrial Hygienists)**  
A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**  
Group 3 - Not Classifiable as to its Carcinogenicity to Humans

**OSHA: (Occupational Safety & Health Administration)**  
X - Present

**Reproductive Toxicity** This product does not contain any known or suspected reproductive hazards.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.

<b>Chronic Toxicity</b>	Repeated exposure may cause skin dryness or cracking. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.
<b>Target Organ Effects</b>	Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Gastrointestinal tract (GI).
<b>Aspiration Hazard</b>	No information available.

**Numerical measures of toxicity - Product**

The following values are calculated based on chapter 3.1 of the GHS document:

<b>LD50 Oral</b>	77256 mg/kg; Acute toxicity estimate
<b>LD50 Dermal</b>	224950 mg/kg; Acute toxicity estimate

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropyl alcohol 67-63-0	EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
D-Limonene 5989-27-5		LC50 96 h: 0.619 - 0.796 mg/L flow-through (Pimephales promelas) LC50 96 h: = 35 mg/L (Oncorhynchus mykiss)		

**Persistence and Degradability** No information available.

**Bioaccumulation** No information available.

Chemical Name	Log Pow
Isopropyl alcohol	0.05

**Other Adverse Effects**

No information available.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** Dispose of in accordance with local regulations.

**Contaminated Packaging** Do not re-use empty containers.

**California Hazardous Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Calcined kaolin clay	Toxic soluble Toxic
Isopropyl alcohol	Toxic Ignitable
D-Limonene	Toxic

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

**TDG** Not regulated

<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Complies

### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

### U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Calcined kaolin clay	66402-68-4	7-13	1.0

### SARA 311/312 Hazard Categories

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Calcined kaolin clay		X		

### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

### U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Methyl alcohol	67-56-1	Developmental
Diethanolamine	111-42-2	Carcinogen

### U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Deodorized kerosene	X	X	X		X
Calcined kaolin clay			X		X
Isopropyl alcohol	X	X	X		X
Mineral Spirits	X	X	X		X
D-Limonene	X			X	

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION**

<b>NFPA</b>	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards *
<b>HMIS</b>	Health Hazard 2	Flammability 1	Physical Hazard 0	Personal Protection X

Prepared By Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

Issuing Date 04-Nov-2013  
Revision Date 24-May-2015  
Revision Note Update to Format.

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**