PANEL & RIVET BONDING (COSMETIC PANELS) STANDARD OPERATING PROCEDURE



Remove spot welds with spot weld cutter. Remove rivets by drilling or grinding. Remove damaged panel and straighten bent flanges with a hammer and dolly.

Dry fit all panels to ensure proper alignment. Drill

holes for replacement rivets or mark locations of

self-piercing rivets.

PRODUCT LIST



PREP

| Part | Product | Size |
|-------|-------------------------------|----------------|
| 38371 | SEM Solve | Gallon |
| 38373 | SEM Solve | 20 oz. Aerosol |
| 38374 | SEM Solve | Square Quart |
| 77771 | XXX Universal Surface Cleaner | Gallon |
| 77774 | XXX Universal Surface Cleaner | Quart |





Clean with SEM Solve or XXX Universal Surface Cleaner. Grind mating flanges with a 36 grit grinding disc at low speed for aggressive grind mark. Remove any adhesive or protective coatings.

i) If rivet bonding, manufacturers may recommend leaving OEM e-coat on the surface of the new panel. If so, scuff with a red scuff pad.

ADHESIVE

| Part | Product | Size |
|-------|--|-----------------|
| 39337 | Dual-Mix Door Skin & SMC Adhesive | 7 oz. Cartridge |
| 39537 | Dual-Mix Weld-Bond Adhesive | 7 oz. Cartridge |
| 39747 | Dual-Mix Multi-Purpose Panel Adhesive | 7 oz. Cartridge |

WATCH & LEARN

REMOVE



Apply 3/8" - 1/2" bead of **Dual-Mix™ Multi-Purpose Panel Adhesive or Dual-Mix Weld-Bond Adhesive** to both surfaces. Use enough material to completely fill the joint when parts are clamped. Tool with a spreader or acid brush. Cover all exposed bare metal.

(i) For smaller parts use **Dual-Mix™ Door Skin & SMC Adhesive**





Clamp panel into place. Do not over clamp. Wipe away excess material.

(i) For maximum bond strength, surfaces must be mated during adhesive's working time.

Clamp panel in place. Install rivets per manufacturer's recommendations during adhesive's working time. Remove clamps after rivets have been installed. Wipe away excess material.



WATCH THE VIDEO AT:

semproducts.com/sop-panelbonding

SEM Products, Inc. Rock Hill, SC 29730 Tech Support: 1-800-831-1122 Customer Care: 1-866-327-7829 semproducts.com

