SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

1 Identification

· Product identifier

· Trade name: 39377 Seam Sealer

· Article number: 39377

- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225
- · Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

S07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

bisphenolA(chloro)oxirane polymer [3-(2,3-epoxypropoxy)propyl]trimethoxysilane 1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane CASTOR OIL GLYCIDAL ETHER

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.


· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 1Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	· Dangerous components:		
25068-38-6	bisphenolA(chloro)oxirane polymer	30-40%	
67762-90-7	FUMED SILICA	5-7%	
26142-30-3	Epoxy Resin	1.5-5%	
68909-14-8	Modified diglycidal ether	1.5-5%	

(Contd. on page 3)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

	(Co	ontd. of page 2)
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	≥1.5-<5%
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	1-1.5%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	≥0.1-<1%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≥0.1-<1%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
25068-38-6 bisphenolA(chloro)oxirane polymer	90 mg/m³
67762-90-7 FUMED SILICA	120 mg/m³
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m^3
107-21-1 ethanediol	30 ppm

USA ·

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(Contd. of page 9.3 mg/m ³
919-30-2 3-aminopropyltriethoxysilane	1.9 mg/m ³
13463-67-7 titanium dioxide	30 mg/m^3
13403-07-7 Ittantum atoxide 1333-86-4 Carbon black	9 mg/m ³
14808-60-7 Quartz (SiO2)	0.075 mg/m
67-56-1 methanol	530 ppm
64-17-5 ethanol	
	1,800 ppm
PAC-2:	
25068-38-6 bisphenolA(chloro)oxirane polymer	990 mg/m³
67762-90-7 FUMED SILICA	1,300 mg/m
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m³
107-21-1 ethanediol	150 ppm
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m³
919-30-2 3-aminopropyltriethoxysilane	21 mg/m³
13463-67-7 titanium dioxide	330 mg/m³
1333-86-4 Carbon black	99 mg/m³
14808-60-7 Quartz (SiO2)	33 mg/m ³
67-56-1 methanol	2,100 ppm
64-17-5 ethanol	3300* ppm
PAC-3:	
25068-38-6 bisphenolA(chloro)oxirane polymer	5,900 mg/m
67762-90-7 FUMED SILICA	7,900 mg/m
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m³
107-21-1 ethanediol	900 ppm
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m³
919-30-2 3-aminopropyltriethoxysilane	350 mg/m ³
13463-67-7 titanium dioxide	2,000 mg/m
1333-86-4 Carbon black	590 mg/m ³
14808-60-7 Quartz (SiO2)	200 mg/m³
67-56-1 methanol	7200* ppm
64-17-5 ethanol	15000* ppn

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 5)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

Information on basis abusinal I	ahamiaal proparties
Information on basic physical and General Information	cnemical properties
Appearance:	
Form:	Liquid
Color:	Dark grey
Odor:	Amine-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>260 °C
Flash point:	257 °C
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density at 20 °C:	1.2528 g/cm³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t er): Not determined.
Viscosity:	
Dynamic at 20 °C:	160,000 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
Water:	0.1 %
VOC content:	0.00 %

(Contd. on page 7)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 6)

Solids content: 99.6 %

• *Other information* No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
13463-67-2	titanium dioxide	2 <i>B</i>
1333-86-4	4 Carbon black	2 <i>B</i>
14808-60-2	7 Quartz (SiO2)	1
64-17	5 ethanol	1
· NTP (Nati	ional Toxicology Program)	
14808-60-2	7 Quartz (SiO2)	K
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water

(Contd. on page 8)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

1 4 70			C	7 ·
	ransport		arma	tion
	uuspul	וטעט	UI III W	עושעו

· UN-Number	
$\cdot DOT$	Void
· ADR, IMDG, IATA	UN3082

· UN proper shipping name

 \cdot **DOT** Void

· ADR 3082 Environmentally hazardous substances, liquid, n.o.s.

· IMDG, IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

· Transport hazard class(es)

 $\cdot DOT$

· Class Void

· ADR, IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles

· Label

· Packing group

· DOT Void · ADR, IMDG, IATA III

• Environmental hazards: Product contains environmentally hazardous substances:

bisphenolA(chloro)oxirane polymer

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

· Special precautions for user Warning: Miscellaneous dangerous substances and articles

· EMS Number: F-A,S-F

(Contd. on page 9)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

	(Contd. of page
· Stowage Category	A
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	11
· DOT · Remarks	ORM-D 49CFR 173.150,156,306
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE. LIQUID, N.O.S., 9, III

1	5 Regulatory information
	· Safety, health and environmental regulations/legislation specific for

Section 355	5 (extremely hazardous substances):	
None of the	e ingredient is listed.	
Section 313	3 (Specific toxic chemical listings):	
68909-14-8	Modified diglycidal ether	
107-21-1	l ethanediol	
67-56-1	l methanol	
TSCA (Tox	cic Substances Control Act):	
25068-38-6	bisphenolA(chloro)oxirane polymer	
1317-65-3	GROUND CALCIUM CARBONATE	
67762-90-7	FUMED SILICA	
26142-30-3	B Epoxy Resin	
68909-14-8	Modified diglycidal ether	
90-72-2	2 2,4,6-tris(dimethylaminomethyl)phenol	
17557-23-2	2 1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	
74398-71-3	CASTOR OIL GLYCIDAL ETHER	
107-21-1	l ethanediol	
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
	3-aminopropyltriethoxysilane	
13463-67-7	titanium dioxide	
1333-86-4	4 Carbon black	

(Contd. on page 10)

SEM

Printing date 07/03/2018 Version number 8

Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

14000 (0.7	(Contd. of page
	Quartz (SiO2)
	methanol
	ethanol
7732-18-5	
	(21st Century Act) (Substances not listed)
	Epoxy Resin
68909-14-8	Modified diglycidal ether
· Proposition	
· Chemicals l	known to cause cancer:
	bisphenolA(chloro)oxirane polymer
74398-71-3	CASTOR OIL GLYCIDAL ETHER
107-21-1	ethanediol
13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO2)
· Chemicals l	known to cause reproductive toxicity for females:
None of the	ingredients is listed.
· Chemicals I	known to cause reproductive toxicity for males:
None of the	ingredients is listed.
· Chemicals l	known to cause developmental toxicity:
107-21-1 e	thanediol
67-56-1 m	ethanol
64-17-5 e	thanol
· Cancerogen	nity categories
· EPA (Envir	conmental Protection Agency)
None of the	ingredients is listed.
· TLV (Thres	hold Limit Value established by ACGIH)
107-21-1	<i>ethanediol</i> A
13463-67-7	titanium dioxide A-
1333-86-4	Carbon black
14808-60-7	Quartz (SiO2)
	ethanol A
· NIOSH-Ca	(National Institute for Occupational Safety and Health)
	titanium dioxide
	Carbon black
	Quartz (SiO2)
	methanol
	elements The product is classified and labeled according to the Globally Harmonized System (GHS)

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 11)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 10)

· Hazard pictograms





· Signal word Danger

· Hazard-determining components of labeling:

bisphenolA(chloro)oxirane polymer

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane 1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

CASTOR OIL GLYCIDAL ETHER

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)

SEM

Printing date 07/03/2018 Version number 8 Reviewed on 07/03/2018

Trade name: 39377 Seam Sealer

(Contd. of page 11)

· Department issuing SDS: Environment protection department.

· Contact: Rita Joiner (rjoiner@semproducts.com)

· Date of preparation / last revision 07/03/2018 / 7

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1A: Carcinogenicity – Category 1A Repr. 2: Reproductive toxicity – Category 2

* * Data compared to the previous version altered.

USA ·