



REFINISH INTERIORS



FORMULATED TO RESTORE OR CHANGE COLOR ON:

Flexible Plastic | Rigid Plastic | Vinyl | Carpet | Velour & More



MIXING SYSTEMS
THOUSANDS OF OEM MATCHED COLORS
AT SEMPRODUCTS.COM/EZMIX



50 POPULAR AEROSOL COLORS & 3 CLEARS



CUSTOM FILL™ AEROSOL BLANK (FILLON MACHINE)



UNIVERSAL COLOR COAT BLANK (OMNI-FILL & OTHERS)







PRFP STEP 1

VINYL & PLASTIC: Clean first with SEM Soap and a gray scuff pad. Rinse with water and allow to dry.

For vinvl, clean thoroughly with Vinvl Prep or XXX Universal Surface Cleaner. using a clean, damp, lintfree towel and wiping in one direction. For plastic, clean with Plastic & Leather Prep or XXX Universal Surface Cleaner.

CARPET & VELOUR: Shampoo first, Clean with **Plastic & Leather Prep.** Scrub lightly with a nylon bristle brush to separate the fibers and to remove oil, grease and contaminants. Allow to dry, then vacuum.

STEP 2 MIXING

DO NOT THIN. **Color Coat** is ready to spray.

Shake or stir well, per label instructions, to ensure color uniformity. For best results, use only when can temperature is approximately 70°F (21°C).

For additional versatility when matching low gloss OEM colors, Color Coat Flattener is available.



SEM Soap

A mild abrasive cleaner for flexible substrates.

ze
6 oz. Tube



Vinvl Prep

A strong solvent blend for refinishing vinyl.

Part	Size
38343	16 oz. Aerosol
38344	Quart



Plastic & Leather Prep

A mild solvent blend to clean plastic and leather.

Part	Size
38351	Square Gallon
38353	16 oz. Aerosol
38354	Cone Top Quart

Size



Color Coat Flattener

An additive that lowers gloss and adds versatility.

Custom Fill+™ High Build

Part Size 62013 16 oz. Aerosol

Part

13038 Pint





Universal Color Part **Coat Blank**

Size 15993 16 oz. Aerosol

A blank aerosol for filling custom Color Coat colors.



AEROSOL: Hold can approximately 6 – 8" from the surface. Apply light coats allowing 5 – 10 minutes between coats.

SPRAY GUN: Using fluid tip size 1.0 - 1.3 at 20 - 25 psi with non-HVLP or 8 - 10 psi at the cap with HVLP, apply 2-3 light coats or until hiding, allowing 5-10 minutes flash time between coats. Some colors will require more coats to cover.

CARPET & VELOUR: Spray one light coat and immediately brush in all directions using a nylon bristle brush. Apply a second light coat and brush again. After surface has completely dried, brush again to loosen fibers.



Mixing System **Cone Top**

For the jobber, shop or mobile technician: 9 toners and 3 clears. Part Size 27979 Cone Top Quart



Mixing System

Quart

For the jobber or shop to start mixing Color Coat.

	Part	Size	
	27989	Quart	
`			

Size



Mixing System Gallon

27969 Gallon

Part

For the jobber or shop that mixes Color Coat regularly.



