PLASTIC TAB REPAIR STANDARD OPERATING PROCEDURE



Clean front and back with Scuff & Clean and damp. gray scuff pad. Rinse with water and dry with clean, lint-free cloth. Clean front and back with SEM Solve, Plastic & Leather Prep or XXX Universal Surface Cleaner. Wipe clean in one direction with dry, lint-free cloth.

PRODUCT LIST



DDED

rner							
Part	Product	Size					
38391	Scuff & Clean	Gallon Pump					
38398	Scuff & Clean	16 oz. Tube					
38371	SEM Solve	Gallon					
38373	SEM Solve	20 oz. Aerosol					
38374	SEM Solve	Square Quart					
38351	Plastic & Leather Prep	Gallon					
38353	Plastic & Leather Prep	16 oz. Aerosol					
38354	Plastic & Leather Prep	Cone Top Quart					
77771	XXX Universal Surface Cleaner	Gallon					
77774	XXX Universal Surface Cleaner	Quart					
39861	Plastic Adhesion Promoter	Gallon					
39863	Plastic Adhesion Promoter	20 oz. Aerosol					
39864	Plastic Adhesion Promoter	Cone Top Quart					
77721	XXX Adhesion Promoter	Gallon					
77723	XXX Adhesion Promoter	16 oz. Aerosol					
77724	XXX Adhesion Promoter	Cone Top Quart					



Grind repair on both sides at low RPM or by hand with P36 grit disc. Drill 1/8" holes in repair area to help "lock in" the repair material. Blow off surface.

- 1 Do not grind too fast and cause plastic to melt.
- (i) For TPO, EPDM, PP and similar plastics, apply Adhesion Promoter as per instructions.



APPLY QUICK SET

Cut enough Plastic Repair Contouring Tape to fold around both sides of the tab. Use permanent marker to trace a good tab for a template.





Λ	D	D	П	•	A ⁻	П	n	N	
н	Г	Г	LI	u	А	ш	u	I۱	

Part	Product	Size
70007	Plastic Repair Contouring Tape	15' Roll
40202	Dual-Mix Quick Set 20	1.7 oz. Cartridge
40207	Dual-Mix Quick Set 20	7 oz. Cartridge
40502	Dual-Mix Quick Set 50	1.7 oz. Cartridge
40507	Dual-Mix Quick Set 50	7 oz. Cartridge
41807	Dual-Mix Quick Set 180	7 oz. Cartridge



Grind the tab back to its original shape and size. Re-drill the bolt hole.





WATCH THE VIDEO AT:

semproducts.com/sop-plastic-tabrepair

> SEM Products, Inc. Rock Hill, SC 29730 Tech Support: 1-800-831-1122 Customer Care: 1-866-327-7829 semproducts.com

