Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

Transparent Plastic Masking Film is a paintable plastic masking film that clings to the substrate for protection from overspray and other contaminants.

FEATURES

- · Transparent film for accurate trimming
- Paintable
- Treated for top coat adhesion
- Clings to substrate
- Easy to dispense box

SUITABLE SUBSTRATES

Any clean, dry, thoroughly cured surface

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Size:
91161	Transparent Plastic Masking Film	Clear	16' x 350'
91201	Transparent Plastic Masking Film	Clear	20' x 350'

Always wear OSHA required (PPE) Personal Protection Equipment as outlined on the SDS and product label to ensure your safety.



HANDLING AND APPLICATION

PREPARATION:

Transparent Plastic Masking Film should only be applied to clean, dry, fully cured surfaces. If vehicle surfaces are dirty, wash and dry before applying plastic sheeting.

Note: Do not apply to wet or dirty vehicles or finishes that are not fully cured.

APPLICATION:

Back-mask jams. Apply sheeting with "paint this side" facing up. Tape down all perimeters. Masking paper can also be used around the perimeters, but is not required. Cut or trim **Transparent Plastic Masking Film**. Apply paint or top coats. Remove film and tape carefully.

Note: Do not apply to wet or dirty vehicles or finishes that are not fully cured.

RELATED PRODUCTS:

Part:	Product Name:	Size:
38351	Plastic & Leather Prep	Gallon
38353	Plastic & Leather Prep	16 oz. Aerosol
38354	Plastic & Leather Prep	Quart
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart
77783	XXX Specialty Adhesive Remover	20 oz. Aerosol
77784	XXX Specialty Adhesive Remover	Quart
77793	XXX Specialty Gel Adhesive Remover	20 oz. Aerosol
91162	Extreme Blue Plastic Masking Film	16' x 350'
91202	Extreme Blue Plastic Masking Film	20' x 350'



STORAGE:

Transparent Plastic Masking Film should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Transparent Plastic Masking Film** is unlimited when stored under normal conditions.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.