

(i) Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

Ez Coat is a direct to metal coating that matches the color and gloss of factory primer and e-coat colors.

FEATURES

- OEM recommended
- Duplicates factory appearance
- Direct to steel and aluminum
- · Quick curing and hiding
- Available in 9 popular OEM colors
- Paintable with most automotive basecoats

SUITABLE SUBSTRATES

- Bare Metal
- OEM finishes
- Primer

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:	
62213	Ez Coat	Black	16 oz. Aerosol	
62223	Ez Coat	Olive Green	16 oz. Aerosol	
62233	Ez Coat	Light Green	16 oz. Aerosol	
62243	Ez Coat	Gray	16 oz. Aerosol	
62253	Ez Coat	Tan	16 oz. Aerosol	
62263	Ez Coat	Olive Brown	16 oz. Aerosol	
62273	Ez Coat	White	16 oz. Aerosol	
62283	Ez Coat	Field Drab	16 oz. Aerosol	
62293	Ez Coat	Dark Green	16 oz. Aerosol	
MIR:		< 1.5		
Category:		EFA		
Coverage:		13 ft² per can @ 1 mils DFT		
Recommended coats:		2–3 coats		
Top coat time:		15 minutes		

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION

PREPARATION:

- 1. Clean surface thoroughly with SEM Solve or XXX Universal Surface Cleaner.
- 2. Sand with P320 grit or finer paper and re-clean with SEM Solve or XXX Universal Surface Cleaner.

APPLICATION:

Coats:	2–3 medium coats
Flash time:	5–10 minutes between coats
Dry time:	30 minutes

Note:

If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button on top of can and spray with button pointed away from you.

After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE:

Ez Coat should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Ez Coat** is 5 years when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:	
38371	SEM Solve	Gallon	
38373	SEM Solve	20 oz. Aerosol	
38374	SEM Solve	Quart	
38375	SEM Solve	5 Gallon	
77763	XXX Universal Gun Cleaner	20 oz. Aerosol	
77771	XXX Universal Surface Cleaner	Gallon	
77774	XXX Universal Surface Cleaner	Quart	

(i) Check local VOC regulations to ensure compliance of all products in your area.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.