



# RUBBERIZED UNDERCOATING

## TECHNICAL DATA SHEET



Check local VOC regulations to ensure compliance of all products in your area.

### DESCRIPTION

Rubberized Undercoating is a premium, paintable, textured coatings for sound dampening, chip resistance, rust protection and corrosion protection.

### FEATURES

- Sound-dampening properties
- Chip and corrosion resistant
- Paintable without bleed through
- Fast-drying
- Uniform final appearance
- Aerosol includes straw for tight spots
- Quality asphalt free formula

### SUITABLE SUBSTRATES

- Properly prepped and primed surfaces

### TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39513	Rubberized Undercoating (Europe Only)	White	24 oz. Aerosol
39523	Rubberized Undercoating	Black	24 oz. Aerosol

	Regulatory	Actual	EU	%
<b>VOC 39513</b>	588 g/L, 4.90 #/gal	588 g/L, 4.90 #/gal	588 g/L	71%
<b>VOC 39523</b>	572 g/L, 4.77 #/gal	572 g/L, 4.77 #/gal	572 g/L	66%

Paintable: Yes

### HANDLING AND APPLICATION

#### PREPARATION:

1. Clean surface with **SEM Solve** or **XXX Universal Surface Cleaner**. Remove any loose paint, rust, oil and grease.
2. Blow off and clean again with **SEM Solve** or **XXX Universal Surface Cleaner**.



Check local VOC regulations to ensure compliance of all products in your area.



## APPLICATION:



### AEROSOL:

<b>Distance:</b>	6 – 8"
<b>Coats:</b>	2 – 3 medium wet
<b>Flash time:</b>	3 – 5 minutes
<b>Top Coat time:</b>	30 minutes

Note: When utilizing any **Rubberized Undercoating** product over 1K coatings, softening or separation may occur. Test in an inconspicuous area for compatibility.

Note: If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.



After each use, turn can upside down and spray several seconds to clear spray tip.



## STORAGE:

**Rubberized Undercoating** should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Rubberized Undercoating** is 3 years when stored under normal conditions.

## RELATED PRODUCTS:

Part:	Product Name:	Size:
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
77763	XXX Universal Gun Cleaner	20 oz. Aerosol
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart



Check local VOC regulations to ensure compliance of all products in your area.

---

### **Technical Consultation Service**

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

---

#### **Disclaimer:**

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.