



DESCRIPTION

Undercoating and **Low VOC Undercoating** are non-paintable, asphalt based aerosol coatings for corrosion protection, chip resistance and sound deadening on automotive frames, wheel wells and undercarriage areas.

FEATURES

- Uniform appearance
- Excellent adhesion
- Economical

SUITABLE SUBSTRATES

- Properly prepped primed or painted surfaces
- Steel
- Aluminum
- SMC
- Fiberglass

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39463	Undercoating	Black	24 oz. Aerosol
40463	Low VOC Undercoating	Black	24 oz. Aerosol
VOC 39463:		3.75 #/gal (450 g/l)	
VOC 40463:		< 40%	
Paintable:		No	

HANDLING AND APPLICATION



PREPARATION:

1. Clean surface with SEM Solve or **XXX Universal Surface Cleaner**. Remove any loose paint, rust, oil and grease.
2. Blow off and clean again with SEM Solve or **XXX Universal Surface Cleaner**.



APPLICATION:

Distance:	8-12"
Coats:	2-3 medium wet
Flash time:	3-5 minutes



Check local VOC regulations to ensure compliance of all products in your area.

Note: If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.



After each use, turn can upside down and spray several seconds to clear spray tip.



STORAGE:

Undercoating and **Low VOC Undercoating** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Undercoating** and **Low VOC Undercoating** is 3 years when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
77763	XXX Universal Gun Cleaner	20 oz. Aerosol
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.