



1 Identification

· **Product identifier**

· **Trade name:** 19363 Toyota Magnetic Gray Pearl 1G3

· **Article number:** 19363

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· **Information department:**

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

2 Hazard identification

· **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carcinogenicity - Category 2

H351 Suspected of causing cancer.

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

acetone
4-methylpentan-2-one
toluene
n-butyl acetate

· **Hazard statements**

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 4
Reactivity = 3

(Contd. on page 3)

CA



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	*1	Health = *1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

67-64-1	acetone	15-40% w/w
68476-86-8	Petroleum gases, liquefied, sweetened	10-30% w/w
123-86-4	n-butyl acetate	5-10% w/w
108-10-1	4-methylpentan-2-one	3-7% w/w
110-19-0	isobutyl acetate	3-7% w/w
763-69-9	ethyl 3-ethoxypropionate	1-5% w/w
108-88-3	toluene	1-5% w/w
108-65-6	2-methoxy-1-methylethyl acetate	0.5-1.5% w/w
100-41-4	ethylbenzene	≤ 1% w/w

4 First aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

CA

(Contd. on page 4)



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

67-64-1 acetone

EL Short-term value: 500 ppm
Long-term value: 250 ppm

EV Short-term value: 750 ppm
Long-term value: 500 ppm

123-86-4 n-butyl acetate

EL Long-term value: 20 ppm

EV Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

(Contd. on page 5)

CA



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 4)

108-10-1 4-methylpentan-2-one

EL Short-term value: 75 ppm
Long-term value: 20 ppm
IARC 2B

EV Short-term value: 75 ppm
Long-term value: 205 mg/m³, 50 ppm

110-19-0 isobutyl acetate

EL Long-term value: 150 ppm
EV Short-term value: 187 ppm
Long-term value: 150 ppm

763-69-9 ethyl 3-ethoxypropionate

EV Long-term value: 300 mg/m³, 50 ppm

108-88-3 toluene

EL Long-term value: 20 ppm
R
EV Long-term value: 20 ppm

108-65-6 2-methoxy-1-methylethyl acetate

EL Short-term value: 75 ppm
Long-term value: 50 ppm
EV Long-term value: 270 mg/m³, 50 ppm

100-41-4 ethylbenzene

EL Long-term value: 20 ppm
IARC 2B
EV Short-term value: 540 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 5)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Color:	Silver-colored
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· **Flash point:** -4 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.9 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.73808 g/cm³

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

(Contd. on page 7)



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 6)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 92.5 %
 - VOC content:** 54.6 %
 - 623.0 g/l / 5.20 lb/gal
- **Solids content:** 7.5 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-10-1	4-methylpentan-2-one	2B
108-88-3	toluene	3
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B

(Contd. on page 8)



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 7)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---|
| · UN-Number | |
| · DOT, TDG, IMDG, IATA | UN1993 |
| · UN proper shipping name | |
| · DOT | Flammable liquids, n.o.s. (Acetone, Petroleum gases, liquefied, sweetened) |
| · TDG | 1993 Flammable liquids, n.o.s. (Acetone, Petroleum gases, liquefied, sweetened) |
| · IMDG, IATA | FLAMMABLE LIQUID, N.O.S. (ACETONE, Petroleum gases, liquefied, sweetened) |

(Contd. on page 9)

CA

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 8)

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids

· **Label**

3

· **TDG, IMDG, IATA**· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**· **DOT, TDG, IMDG, IATA**

II

· **Environmental hazards:**· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Flammable liquids

· **EMS Number:**

F-E, S-E

· **Stowage Category**

B

· **Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **TDG**· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ACETONE,
PETROLEUM GASES, LIQUEFIED, SWEETENED), 3, II

CA

(Contd. on page 10)



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 9)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-10-1	4-methylpentan-2-one
	Acrylic Resin
108-88-3	toluene
7429-90-5	aluminium
1330-20-7	xylene
100-41-4	ethylbenzene
147-14-8	Phthalocyanine Blue
71-36-3	butan-1-ol
7727-43-7	barium sulphate, natural

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
123-86-4	n-butyl acetate
108-10-1	4-methylpentan-2-one
110-19-0	isobutyl acetate
763-69-9	ethyl 3-ethoxypropionate
108-88-3	toluene
9004-36-8	Cellulose Acetate Butyrate
108-65-6	2-methoxy-1-methylethyl acetate
110-43-0	heptan-2-one
7429-90-5	aluminium
1330-20-7	xylene
16883-83-3	benzyl 3-isobutyroxy-1-isopropyl-2-2-dimethylpropyl phthalate
1333-86-4	Carbon black
100-41-4	ethylbenzene
6358-30-1	Violet Pigment
147-14-8	Phthalocyanine Blue
71-36-3	butan-1-ol
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate
104810-48-2	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy-
7727-43-7	barium sulphate, natural
104810-47-1	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidiny) sebacate
25322-68-3	Polyethylene glycol

(Contd. on page 11)

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 10)

106-79-6	Dimethyl sebacate(Impurity)
2403-89-6	4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

67-64-1	acetone
68476-86-8	Petroleum gases, liquefied, sweetened
123-86-4	n-butyl acetate
108-10-1	4-methylpentan-2-one
110-19-0	isobutyl acetate
763-69-9	ethyl 3-ethoxypropionate
108-88-3	toluene
108-65-6	2-methoxy-1-methylethyl acetate
110-43-0	heptan-2-one
7429-90-5	aluminium
1330-20-7	xylene
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1333-86-4	Carbon black
100-41-4	ethylbenzene
6358-30-1	Violet Pigment
147-14-8	Phthalocyanine Blue
71-36-3	butan-1-ol
8052-41-3	Stoddard solvent
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
104810-48-2	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy-
7727-43-7	barium sulphate, natural
104810-47-1	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
25322-68-3	Polyethylene glycol
106-79-6	Dimethyl sebacate(Impurity)

· **Canadian Ingredient Disclosure list (limit 0.1%)**

100-41-4	ethylbenzene
----------	--------------

· **Canadian Ingredient Disclosure list (limit 1%)**

67-64-1	acetone
123-86-4	n-butyl acetate
108-10-1	4-methylpentan-2-one
110-19-0	isobutyl acetate
108-88-3	toluene

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

CA



Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 11)

· **Hazard pictograms**



GHS02

GHS04

GHS07

GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*acetone**4-methylpentan-2-one**toluene**n-butyl acetate*

· **Hazard statements**

*H222 Extremely flammable aerosol.**H280 Contains gas under pressure; may explode if heated.**H319 Causes serious eye irritation.**H351 Suspected of causing cancer.**H361 Suspected of damaging fertility or the unborn child.**H336 May cause drowsiness or dizziness.**H373 May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

*P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Do not pierce or burn, even after use.**P260 Do not breathe dust/fume/gas/mist/vapours/spray.**P264 Wash thoroughly after handling.**P271 Use only outdoors or in a well-ventilated area.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P312 Call a POISON CENTER/doctor if you feel unwell.**P314 Get medical advice/attention if you feel unwell.**P337+P313 If eye irritation persists: Get medical advice/attention.**P403+P233 Store in a well-ventilated place. Keep container tightly closed.**P405 Store locked up.**P410+P403 Protect from sunlight. Store in a well-ventilated place.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 13)

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19363 Toyota Magnetic Gray Pearl 1G3

(Contd. of page 12)

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/20/2017 / 3

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

· *** Data compared to the previous version altered.**

CA