

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

1 Identification

- **Product identifier**
- **Trade name:** 42280 1.7 VOC Rockit Liner kit with hardener
- **Article number:** 42280 Kit
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Respiratory Sensitizer - Category 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure - Category 2

H371 May cause damage to organs.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - Category 3

H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

CA

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS08 GHS07

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

HDI Prepolymer

CERAMIC MICROSPHERES

Talc

n-butyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H335 May cause respiratory irritation.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

P243 Take actions to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 3)

CA



Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 2)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 3

Reactivity = 0

3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

540-88-5	tert-butyl acetate	10-30% w/w
28182-81-2	HDI Prepolymer	7-13% w/w
66402-68-4	CERAMIC MICROSPHERES	7-13% w/w
14807-96-6	Talc	5-10% w/w
123-86-4	n-butyl acetate	5-10% w/w
67-64-1	acetone	1-5% w/w
	POLYESTER RESIN	1-5% w/w
	POLYESTER RESIN	1-5% w/w
110-43-0	heptan-2-one	1-5% w/w
108-88-3	toluene	≤ 1% w/w

4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

CA



Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

540-88-5 tert-butyl acetate

EL Long-term value: 200 ppm

EV Long-term value: 950 mg/m³, 200 ppm

123-86-4 n-butyl acetate

EL Long-term value: 20 ppm

EV Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

67-64-1 acetone

EL Short-term value: 500 ppm

Long-term value: 250 ppm

EV Short-term value: 750 ppm

Long-term value: 500 ppm

110-43-0 heptan-2-one

EL Long-term value: 50 ppm

EV Long-term value: 115 mg/m³, 25 ppm

108-88-3 toluene

EL Long-term value: 20 ppm

R

EV Long-term value: 20 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

97 °C

· **Flash point:**

15 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

370 °C

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:

2.6 Vol %

Upper:

13.0 Vol %

· **Vapor pressure at 20 °C:**

41 hPa

· **Density at 20 °C:**

1.2667 g/cm³

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

Water:

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:

Not determined.

Kinematic:

Not determined.

(Contd. on page 7)



Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 6)

· **Solvent content:**

Organic solvents:	37.7 %
Water:	0.1 %
VOC content:	10.9 %
	147.1 g/l / 1.23 lb/gl

Solids content: 62.3 %

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

28182-81-2 HDI Prepolymer

Oral	LD50	1000 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	LC50/4 h	137-1150 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
108-88-3	toluene	3
111-76-2	2-butoxyethanol	3

(Contd. on page 8)



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 7)

100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO ₂)	I
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, TDG, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **TDG** 1263 Paint, special provision 640D
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids

(Contd. on page 9)

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 8)

- **Label** 3
- **TDG, IMDG**



- **Class** 3 Flammable liquids
- **Label** 3

- **IATA**



- **Class** 3 Flammable liquids
- **Label** 3

- **Packing group**
- **DOT, TDG, IMDG, IATA** II

- **Environmental hazards:** Product contains environmentally hazardous substances: HDI Prepolymer
- **Marine pollutant:** Yes
Symbol (fish and tree)
- **Special marking (TDG):** Symbol (fish and tree)

- **Special precautions for user** Warning: Flammable liquids
- **EMS Number:** F-E,S-E
- **Stowage Category** B

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

- **TDG**
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

CA

(Contd. on page 10)



Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 9)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

	Acrylic Resin
14807-96-6	Talc
1330-20-7	xylene
108-88-3	toluene
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
822-06-0	hexamethylene-di-isocyanate

· **TSCA (Toxic Substances Control Act):**

540-88-5	tert-butyl acetate
28182-81-2	HDI Prepolymer
66402-68-4	CERAMIC MICROSPHERES
1317-65-3	GROUND CALCIUM CARBONATE
14807-96-6	Talc
123-86-4	n-butyl acetate
67-64-1	acetone
110-43-0	heptan-2-one
108-65-6	2-methoxy-1-methylethyl acetate
1330-20-7	xylene
1333-86-4	Carbon black
108-88-3	toluene
77-58-7	dibutyltin dilaurate
9038-95-3	OXIRANE,ME, POLYMER
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
14808-60-7	Quartz (SiO ₂)
822-06-0	hexamethylene-di-isocyanate
108-83-8	2,6-dimethylheptan-4-one
19549-80-5	4,6-dimethylheptan-2-one
7732-18-5	water

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

28182-81-2	HDI Prepolymer
66402-68-4	CERAMIC MICROSPHERES
14807-96-6	Talc
123-86-4	n-butyl acetate

(Contd. on page 11)



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 10)

67-64-1	acetone
110-43-0	heptan-2-one
108-65-6	2-methoxy-1-methylethyl acetate
1330-20-7	xylene
1333-86-4	Carbon black
112945-52-5	SILICA
108-88-3	toluene
77-58-7	dibutyltin dilaurate
9038-95-3	OXIRANE,ME, POLYMER
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
14808-60-7	Quartz (SiO ₂)
822-06-0	hexamethylene-di-isocyanate
108-83-8	2,6-dimethylheptan-4-one
19549-80-5	4,6-dimethylheptan-2-one
7732-18-5	water

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

540-88-5	tert-butyl acetate
123-86-4	n-butyl acetate
67-64-1	acetone
110-43-0	heptan-2-one

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS08 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

HDI Prepolymer

CERAMIC MICROSPHERES

Talc

n-butyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H335 May cause respiratory irritation.

(Contd. on page 12)

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rockit Liner kit with hardener

(Contd. of page 11)

· Precautionary statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.
- P243 Take actions to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/20/2017 / 6

· Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

(Contd. on page 13)

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 42280 1.7 VOC Rokit Liner kit with hardener

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

(Contd. of page 12)

· *** Data compared to the previous version altered.**

CA