

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

1 Identification

- **Product identifier**
- **Trade name:** 39143 Trim Black
- **Article number:** 39143
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard - Category 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

toluene
acetone
butanone
n-butyl acetate

· **Hazard statements**

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)



Trade name: 39143 Trim Black

(Contd. of page 2)

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

67-64-1	acetone	15-40% w/w
68476-86-8	Petroleum gases, liquefied, sweetened	10-30% w/w
108-88-3	toluene	10-30% w/w
110-19-0	isobutyl acetate	5-10% w/w
1330-20-7	xylene	1-5% w/w
78-93-3	butanone	1-5% w/w
123-86-4	n-butyl acetate	0.5-1.5% w/w

4 First aid measures

· **Description of first aid measures**

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

67-64-1 acetone

EL	Short-term value: 500 ppm Long-term value: 250 ppm
EV	Short-term value: 750 ppm Long-term value: 500 ppm

108-88-3 toluene

EL	Long-term value: 20 ppm
R	

(Contd. on page 5)

CA



Trade name: 39143 Trim Black

(Contd. of page 4)

EV	Long-term value: 20 ppm
110-19-0 isobutyl acetate	
EL	Long-term value: 150 ppm
EV	Short-term value: 187 ppm
	Long-term value: 150 ppm
1330-20-7 xylene	
EL	Short-term value: 150 ppm
	Long-term value: 100 ppm
EV	Short-term value: 650 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
78-93-3 butanone	
EL	Short-term value: 100 ppm
	Long-term value: 50 ppm
EV	Short-term value: 885 mg/m ³ , 300 ppm
	Long-term value: 590 mg/m ³ , 200 ppm
123-86-4 n-butyl acetate	
EL	Long-term value: 20 ppm
EV	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Trade name: 39143 Trim Black

(Contd. of page 5)

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Color: Black

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 405 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 13.0 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.74751 g/cm³

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 92.0 %

(Contd. on page 7)



Trade name: 39143 Trim Black

(Contd. of page 6)

VOC content:	60.7 % 645.0 g/l / 5.38 lb/gl
Solids content:	7.9 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
68855-54-9	diatomaceous earth	GROUP 1
9002-88-4	Polyethylene low density	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

68855-54-9	diatomaceous earth	HUMAN CARCINOGEN
------------	--------------------	------------------

(Contd. on page 8)



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 7)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---------------------|
| · UN-Number | |
| · DOT, TDG, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · DOT | Aerosols, flammable |
| · TDG | 1950 Aerosols |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

- **Transport hazard class(es)**

- **DOT**



- | | |
|----------------|-----|
| · Class | 2.1 |
| · Label | 2.1 |

(Contd. on page 9)

CA

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 8)

· TDG (Transport dangerous goods):



- Class 2 5F Gases
- Label 2.1

· IMDG, IATA



- Class 2.1
- Label 2.1

· Packing group

- DOT, TDG, IMDG, IATA Void

· Environmental hazards:

- Marine pollutant: No

· Special precautions for user

· EMS Number:

· Stowage Code

Warning: Gases

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of living
quarters.

· Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for
division 1.4. For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2. For
WASTE AEROSOLS: Segregation as for the appropriate subdivision
of class 2.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· TDG

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

(Contd. on page 10)

CA



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 9)

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
	Acrylic Resin
1330-20-7	xylene
78-93-3	butanone
111-76-2	2-butoxyethanol
67-56-1	methanol
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
108-88-3	toluene
110-19-0	isobutyl acetate
1330-20-7	xylene
78-93-3	butanone
123-86-4	n-butyl acetate
16883-83-3	benzyl 3-isobutyloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1333-86-4	Carbon black
68611-44-9	Modified Silica
111-76-2	2-butoxyethanol
68855-54-9	diatomaceous earth
9002-88-4	Polyethylene low density
67-56-1	methanol
100-41-4	ethylbenzene
7732-18-5	water

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

67-64-1	acetone
68476-86-8	Petroleum gases, liquefied, sweetened
108-88-3	toluene
110-19-0	isobutyl acetate
1330-20-7	xylene
78-93-3	butanone
123-86-4	n-butyl acetate

(Contd. on page 11)

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 10)

16883-83-3	benzyl 3-isobutyloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1333-86-4	Carbon black
68611-44-9	Modified Silica
111-76-2	2-butoxyethanol
68855-54-9	diatomaceous earth
9002-88-4	Polyethylene low density
67-56-1	methanol
100-41-4	ethylbenzene
7732-18-5	water

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

67-64-1	acetone
108-88-3	toluene
110-19-0	isobutyl acetate
78-93-3	butanone
123-86-4	n-butyl acetate

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene

acetone

butanone

n-butyl acetate

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

(Contd. on page 12)

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 39143 Trim Black

(Contd. of page 11)

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see on this label).
 P331 Do NOT induce vomiting.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Steve Gaver (sgaver@semproducts.com)
- **Date of preparation / last revision** 06/20/2017 / 8
- **Abbreviations and acronyms:**
 - ICAO: International Civil Aviation Organisation
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
- *** Data compared to the previous version altered.**

CA