

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

1 Identification

· Product identifier

· Trade name: 61983 2K Color Coat Custom Fill

· Article number: 61983 2K

· Application of the substance / the mixture Coating

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Respiratory Sensitizer - Category 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ Cell Mutagenicity - Category 1B

H340 May cause genetic defects.

Carcinogenicity - Category 1B

H350 May cause cancer.

Specific Target Organ Toxicity - Single Exposure - Category 2

H371 May cause damage to organs.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

(Contd. on page 2)

CA

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 1)

Specific Target Organ Toxicity - Single Exposure -
Category 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS08 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

HDI Prepolymer

acetone

Solvent naphtha (petroleum), light arom.

POLYMERIC MDI

Aromatic Polyisocyanate

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomers and homologues

methylenediphenyl diisocyanate

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 3)

-CA-

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 2)

- P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:

67-64-1	acetone	15-40% w/w
74-98-6	propane	10-30% w/w
28182-81-2	HDI Prepolymer	10-30% w/w
53862-89-8	POLYMERIC MDI	3-7% w/w
110-19-0	isobutyl acetate	1-5% w/w
64742-95-6	Solvent naphtha (petroleum), light arom.	1-5% w/w
127821-00-5	Aromatic Polyisocyanate	1-5% w/w
101-68-8	4,4'-methylenediphenyl diisocyanate	0.5-1.5% w/w
95-63-6	1,2,4-trimethylbenzene	0.5-1.5% w/w
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	≤ 1% w/w
26447-40-5	methylenediphenyl diisocyanate	≤ 1% w/w

CA

(Contd. on page 4)



Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 3)

4 First aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)

CA



Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

67-64-1 acetone

EL	Short-term value: 500 ppm Long-term value: 250 ppm
EV	Short-term value: 750 ppm Long-term value: 500 ppm

74-98-6 propane

EL	Long-term value: 1000 ppm
EV	Long-term value: 1.000 ppm

110-19-0 isobutyl acetate

EL	Long-term value: 150 ppm
EV	Short-term value: 187 ppm Long-term value: 150 ppm

101-68-8 4,4'-methylenediphenyl diisocyanate

EL	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S
EV	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

Breathing equipment:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

CA



Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44.5 °C

· **Flash point:** -97 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 405 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.7 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 8300 hPa

· **Density at 20 °C:** 0.76026 g/cm³

(Contd. on page 7)



Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 6)

· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	70.2 %
VOC content:	36.9 %
	412.7 g/l / 3.44 lb/gal
Solids content:	29.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

28182-81-2 HDI Prepolymer

Oral	LD50	1000 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	LC50/4 h	137-1150 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

(Contd. on page 8)



Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 7)

· **Sensitization:**

Sensitization possible through inhalation.
Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

101-68-8	4,4'-methylenediphenyl diisocyanate	3
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
98-82-8	cumene	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
584-84-9	4-methyl-m-phenylene diisocyanate	R

*

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

CA

(Contd. on page 9)

Safety Data Sheet

according to HPR, Schedule 1









Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 8)

14 Transport information

· UN-Number	UN1950
· DOT, TDG, IMDG, IATA	
· UN proper shipping name	Aerosols, flammable
· DOT	1950 Aerosols
· TDG	AEROSOLS (HDI Prepolymer, 1,2,4-trimethylbenzene)
· IMDG	AEROSOLS, flammable
· IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	2.1
· Label	2.1
· TDG (Transport dangerous goods):	
 	
· Class	2 5F Gases
· Label	2.1
· IMDG	
 	
· Class	2.1
· Label	2.1
· IATA	
	
· Class	2.1
· Label	2.1
· Packing group	
· DOT, TDG, IMDG, IATA	Void
· Environmental hazards:	Product contains environmentally hazardous substances: HDI Prepolymer
· Marine pollutant:	No
· Special marking (TDG):	Symbol (fish and tree)
· Special precautions for user	Warning: Gases

(Contd. on page 10)

CA

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 9)

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· TDG	
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

584-84-9	4-methyl-m-phenylene diisocyanate
----------	-----------------------------------

· Section 313 (Specific toxic chemical listings):

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

95-63-6	1,2,4-trimethylbenzene
---------	------------------------

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
-----------	------------------------------------------------------

	Acrylic Resin
--	---------------

26447-40-5	methylenediphenyl diisocyanate
------------	--------------------------------

1330-20-7	xylene
-----------	--------

98-82-8	cumene
---------	--------

584-84-9	4-methyl-m-phenylene diisocyanate
----------	-----------------------------------

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
---------	---------

(Contd. on page 11)

CA

Safety Data Sheet
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 10)

74-98-6	propane
28182-81-2	HDI Prepolymer
53862-89-8	POLYMERIC MDI
110-19-0	isobutyl acetate
64742-95-6	Solvent naphtha (petroleum), light arom.
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer
127821-00-5	Aromatic Polyisocyanate
101-68-8	4,4'-methylenediphenyl diisocyanate
95-63-6	1,2,4-trimethylbenzene
763-69-9	ethyl 3-ethoxypropionate
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
108-67-8	mesitylene
165101-57-5	Mono-Oxazolidine
26447-40-5	methylenediphenyl diisocyanate
1333-86-4	Carbon black
1330-20-7	xylene
108-83-8	2,6-dimethylheptan-4-one
98-82-8	cumene
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
584-84-9	4-methyl-m-phenylene diisocyanate

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

67-64-1	acetone
74-98-6	propane
28182-81-2	HDI Prepolymer
53862-89-8	POLYMERIC MDI
110-19-0	isobutyl acetate
64742-95-6	Solvent naphtha (petroleum), light arom.
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer
127821-00-5	Aromatic Polyisocyanate
101-68-8	4,4'-methylenediphenyl diisocyanate
95-63-6	1,2,4-trimethylbenzene
763-69-9	ethyl 3-ethoxypropionate
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
108-67-8	mesitylene
26447-40-5	methylenediphenyl diisocyanate
1333-86-4	Carbon black
1330-20-7	xylene
108-83-8	2,6-dimethylheptan-4-one
98-82-8	cumene
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy

(Contd. on page 12)

CA

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 11)

584-84-9	4-methyl-m-phenylene diisocyanate
· Canadian Ingredient Disclosure list (limit 0.1%)	
101-68-8	4,4'-methylenediphenyl diisocyanate
95-63-6	1,2,4-trimethylbenzene
108-67-8	mesitylene
· Canadian Ingredient Disclosure list (limit 1%)	
67-64-1	acetone
110-19-0	isobutyl acetate

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS08 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

HDI Prepolymer

acetone

Solvent naphtha (petroleum), light arom.

POLYMERIC MDI

Aromatic Polyisocyanate

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomeres and homologues

methylenediphenyl diisocyanate

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 13)

Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 61983 2K Color Coat Custom Fill

(Contd. of page 12)

- P284 [In case of inadequate ventilation] wear respiratory protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see on this label).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/20/2017 / 10

· **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

· *** Data compared to the previous version altered.**