



## 1 Identification

- **Product identifier**
- **Trade name:** 19173 Honda Desert Mist Metallic YR538M
- **Article number:** 19173
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Germ Cell Mutagenicity - Category 1B

H340 May cause genetic defects.

Carcinogenicity - Category 1B

H350 May cause cancer.

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19173 Honda Desert Mist Metallic YR538M

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

acetone  
4-methylpentan-2-one  
toluene  
Stoddard solvent

· **Hazard statements**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

CA



**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 2)

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



### 3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

|            |                                       |            |
|------------|---------------------------------------|------------|
| 67-64-1    | acetone                               | 15-40% w/w |
| 68476-86-8 | Petroleum gases, liquefied, sweetened | 10-30% w/w |
| 123-86-4   | n-butyl acetate                       | 5-10% w/w  |
| 108-10-1   | 4-methylpentan-2-one                  | 3-7% w/w   |
| 110-19-0   | isobutyl acetate                      | 3-7% w/w   |
| 763-69-9   | ethyl 3-ethoxypropionate              | 1-5% w/w   |
| 108-88-3   | toluene                               | 1-5% w/w   |
| 7429-90-5  | aluminium                             | 1-5% w/w   |
| 100-41-4   | ethylbenzene                          | ≤ 1% w/w   |
| 8052-41-3  | Stoddard solvent                      | ≤ 1% w/w   |

### 4 First aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

CA

(Contd. on page 4)



**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 3)

## 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

CA



**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

|    |   |
|----|---|
| EL | Short-term value: 500 ppm<br>Long-term value: 250 ppm |
| EV | Short-term value: 750 ppm<br>Long-term value: 500 ppm |

**123-86-4 n-butyl acetate**

|    |   |
|----|---|
| EL | Long-term value: 20 ppm   |
| EV | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |

**108-10-1 4-methylpentan-2-one**

|    |   |
|----|---|
| EL | Short-term value: 75 ppm<br>Long-term value: 20 ppm<br>IARC 2B              |
| EV | Short-term value: 75 ppm<br>Long-term value: 205 mg/m <sup>3</sup> , 50 ppm |

**110-19-0 isobutyl acetate**

|    |   |
|----|---|
| EL | Long-term value: 150 ppm                              |
| EV | Short-term value: 187 ppm<br>Long-term value: 150 ppm |

**763-69-9 ethyl 3-ethoxypropionate**

|    |   |
|----|---|
| EV | Long-term value: 300 mg/m <sup>3</sup> , 50 ppm |
|----|---|

**108-88-3 toluene**

|    |                              |
|----|------------------------------|
| EL | Long-term value: 20 ppm<br>R |
| EV | Long-term value: 20 ppm      |

**100-41-4 ethylbenzene**

|    |   |
|----|---|
| EL | Long-term value: 20 ppm<br>IARC 2B  |
| EV | Short-term value: 540 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |

**8052-41-3 Stoddard solvent**

|    |   |
|----|---|
| EL | Short-term value: 580 mg/m <sup>3</sup><br>Long-term value: 290 mg/m <sup>3</sup> |
| EV | Long-term value: 525 mg/m <sup>3</sup>  |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.

(Contd. on page 6)



**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 5)

*Avoid contact with the eyes and skin.*

· **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

· **Protection of hands:**

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



*Protective gloves*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**

*Safety glasses*



*Tightly sealed goggles*

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

|                        |                        |
|------------------------|------------------------|
| <b>Form:</b>           | <i>Aerosol</i>         |
| <b>Color:</b>          | <i>Light beige</i>     |
| <b>Odor:</b>           | <i>Characteristic</i>  |
| <b>Odor threshold:</b> | <i>Not determined.</i> |

· **pH-value:** *Not determined.*

· **Change in condition**

|                                     |                      |
|-------------------------------------|----------------------|
| <b>Melting point/Melting range:</b> | <i>Undetermined.</i> |
| <b>Boiling point/Boiling range:</b> | <i>55 °C</i>         |

· **Flash point:** *-103 °C*

· **Flammability (solid, gaseous):** *Not applicable.*

· **Ignition temperature:** *370 °C*

· **Decomposition temperature:** *Not determined.*

· **Auto igniting:** *Product is not selfigniting.*

(Contd. on page 7)

# Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19173 Honda Desert Mist Metallic YR538M

(Contd. of page 6)

|   |   |
|---|---|
| · <b>Danger of explosion:</b>                     | <i>In use, may form flammable/explosive vapour-air mixture.</i> |
| · <b>Explosion limits:</b>                        |   |
| Lower:  | 1.9 Vol %   |
| Upper:  | 13.0 Vol %  |
| · <b>Vapor pressure at 20 °C:</b>                 | 233 hPa   |
| · <b>Density at 20 °C:</b>                        | 0.74139 g/cm <sup>3</sup>                                       |
| · <b>Relative density</b>                         | Not determined.   |
| · <b>Vapor density</b>                            | Not determined.   |
| · <b>Evaporation rate</b>                         | Not applicable.   |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.                               |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.   |
| · <b>Viscosity:</b>                               |   |
| Dynamic:  | Not determined.   |
| Kinematic:  | Not determined.   |
| · <b>Solvent content:</b>                         |   |
| Organic solvents:                                 | 92.2 %  |
| VOC content:                                      | 54.3 %  |
|   | 625.0 g/l / 5.22 lb/gl  |
| Solids content:                                   | 7.8 %   |
| · <b>Other information</b>                        | No further relevant information available.                      |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
  - Nitrogen oxides
  - Hydrocarbons
  - Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

| 108-88-3 toluene |          |                      |
|------------------|----------|----------------------|
| Oral             | LD50     | 5000 mg/kg (rat)     |
| Dermal           | LD50     | 12124 mg/kg (rabbit) |
| Inhalative       | LC50/4 h | 5320 mg/l (mouse)    |

(Contd. on page 8)





**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 7)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
The product can cause inheritable damage.
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

|            |                                      |                                     |
|------------|--------------------------------------|-------------------------------------|
| 108-10-1   | 4-methylpentan-2-one                 | 2B                                  |
| 108-88-3   | toluene                              | 3                                   |
| 1330-20-7  | xylene                               | 3                                   |
| 100-41-4   | ethylbenzene                         | 2B                                  |
| 1309-37-1  | diiron trioxide                      | 3                                   |
| 1333-86-4  | Carbon black                         | 2B                                  |
| 13463-67-7 | titanium dioxide                     | 2B                                  |
| 7631-86-9  | silicon dioxide, chemically prepared | 3                                   |
|            | BENTONITE                            | suspected carcinogen <2% 14808-60-7 |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

CA



**Safety Data Sheet**  
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 8)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, TDG, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **TDG** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1
- **TDG (Transport dangerous goods):**



- **Class** 2 5F Gases
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

- **Packing group**
- **DOT, TDG, IMDG, IATA** Void

- **Environmental hazards:**
- **Marine pollutant:** No

- **Special precautions for user** Warning: Gases
- **EMS Number:** F-D,S-U

(Contd. on page 10)

CA



**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 9)

|  |  |
|--|--|
| · <b>Stowage Code</b>  | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.   |
| · <b>Segregation Code</b>  | SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.  |
| · <b>Transport/Additional information:</b>                                       |  |
| · <b>DOT</b>   |  |
| · <b>Quantity limitations</b>  | On passenger aircraft/rail: 75 kg<br>On cargo aircraft only: 150 kg  |
| · <b>TDG</b>   |  |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity   |
| · <b>IMDG</b>  |  |
| · <b>Limited quantities (LQ)</b>   | 1L   |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity   |
| · <b>UN "Model Regulation":</b>  | UN 1950 AEROSOLS, 2.1  |

## **15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

### · **Section 313 (Specific toxic chemical listings):**

|           |                      |
|-----------|----------------------|
| 108-10-1  | 4-methylpentan-2-one |
| 108-88-3  | toluene              |
|           | Acrylic Resin        |
| 7429-90-5 | aluminium            |
| 1330-20-7 | xylene               |
| 100-41-4  | ethylbenzene         |
| 71-36-3   | butan-1-ol           |

### · **TSCA (Toxic Substances Control Act):**

|          |                      |
|----------|----------------------|
| 67-64-1  | acetone              |
| 123-86-4 | n-butyl acetate      |
| 108-10-1 | 4-methylpentan-2-one |

(Contd. on page 11)

**Safety Data Sheet**  
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 10)

|             |  |
|-------------|--|
| 110-19-0    | isobutyl acetate   |
| 763-69-9    | ethyl 3-ethoxypropionate   |
| 108-88-3    | toluene  |
| 9004-36-8   | Cellulose Acetate Butyrate   |
| 7429-90-5   | aluminium  |
| 110-43-0    | heptan-2-one   |
| 1330-20-7   | xylene   |
| 16883-83-3  | benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate   |
| 100-41-4    | ethylbenzene   |
| 8052-41-3   | Stoddard solvent   |
| 108-65-6    | 2-methoxy-1-methylethyl acetate  |
| 1309-37-1   | diiron trioxide  |
| 71-36-3     | butan-1-ol   |
| 41556-26-7  | bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate  |
| 1333-86-4   | Carbon black   |
| 104810-48-2 | poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy-   |
| 13463-67-7  | titanium dioxide   |
| 104810-47-1 | poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- |
| 64742-88-7  | Solvent naphtha (petroleum), medium aliph.   |
| 6358-30-1   | Violet Pigment   |
| 82919-37-7  | Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate  |
| 25322-68-3  | Polyethylene glycol  |
| 7631-86-9   | silicon dioxide, chemically prepared   |
| 106-79-6    | Dimethyl sebacate(Impurity)  |
| 2403-89-6   | 4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)   |
| 9038-95-3   | OXIRANE,ME, POLYMER  |
| 19549-80-5  | 4,6-dimethylheptan-2-one   |

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

|            |                                       |
|------------|---------------------------------------|
| 67-64-1    | acetone                               |
| 68476-86-8 | Petroleum gases, liquefied, sweetened |
| 123-86-4   | n-butyl acetate                       |
| 108-10-1   | 4-methylpentan-2-one                  |
| 110-19-0   | isobutyl acetate                      |
| 763-69-9   | ethyl 3-ethoxypropionate              |
| 108-88-3   | toluene                               |
| 7429-90-5  | aluminium                             |
| 110-43-0   | heptan-2-one                          |
| 1330-20-7  | xylene                                |

(Contd. on page 12)

CA

**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 11)

|             |  |
|-------------|--|
| 16883-83-3  | benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate   |
| 8052-41-3   | Stoddard solvent   |
| 100-41-4    | ethylbenzene   |
| 8052-41-3   | Stoddard solvent   |
| 108-65-6    | 2-methoxy-1-methylethyl acetate  |
| 1309-37-1   | diiron trioxide  |
| 71-36-3     | butan-1-ol   |
| 41556-26-7  | bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate  |
| 1333-86-4   | Carbon black   |
| 104810-48-2 | poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy-   |
| 13463-67-7  | titanium dioxide   |
| 104810-47-1 | poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- |
| 64742-88-7  | Solvent naphtha (petroleum), medium aliph.   |
| 6358-30-1   | Violet Pigment   |
| 82919-37-7  | Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate  |
| 25322-68-3  | Polyethylene glycol  |
| 7631-86-9   | silicon dioxide, chemically prepared   |
| 106-79-6    | Dimethyl sebacate(Impurity)  |
| 9038-95-3   | OXIRANE,ME, POLYMER  |
| 19549-80-5  | 4,6-dimethylheptan-2-one   |

· **Canadian Ingredient Disclosure list (limit 0.1%)**

|          |              |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

· **Canadian Ingredient Disclosure list (limit 1%)**

|           |                      |
|-----------|----------------------|
| 67-64-1   | acetone              |
| 123-86-4  | n-butyl acetate      |
| 108-10-1  | 4-methylpentan-2-one |
| 110-19-0  | isobutyl acetate     |
| 108-88-3  | toluene              |
| 7429-90-5 | aluminium            |

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

acetone

4-methylpentan-2-one

(Contd. on page 13)

# Safety Data Sheet

according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

Trade name: 19173 Honda Desert Mist Metallic YR538M

(Contd. of page 12)

toluene

Stoddard solvent

## Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

## Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## National regulations:

## Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

## Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

## Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

\*

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection department.

Contact: Steve Gaver (sgaver@semproducts.com)

Date of preparation / last revision 06/20/2017 / 14

(Contd. on page 14)

CA

**Safety Data Sheet**  
according to HPR, Schedule 1



Printing date 06/20/2017

Reviewed on 06/20/2017

**Trade name: 19173 Honda Desert Mist Metallic YR538M**

(Contd. of page 13)

**· Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative

**· \* Data compared to the previous version altered.**

CA