

## 1 Identification

- **Product identifier**
- **Trade name:** HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06
- **Article number:** HR010 Kit
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT SE 2 H371 May cause damage to organs.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS08



GHS07

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*HDI Prepolymer*

*n-butyl acetate*

*Solvent naphtha (petroleum), light arom.*

*acetone*

*bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate*

· **Hazard statements**

*H225 Highly flammable liquid and vapor.*

*H315 Causes skin irritation.*

*H319 Causes serious eye irritation.*

*H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

*H317 May cause an allergic skin reaction.*

*H340 May cause genetic defects.*

*H350 May cause cancer.*

*H371 May cause damage to organs.*

*H336 May cause drowsiness or dizziness.*

· **Precautionary statements**

*P201 Obtain special instructions before use.*

*P202 Do not handle until all safety precautions have been read and understood.*

*P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.*

*P233 Keep container tightly closed.*

*P240 Ground/bond container and receiving equipment.*

*P241 Use explosion-proof electrical/ventilating/lighting/equipment.*

*P242 Use only non-sparking tools.*

*P243 Take precautionary measures against static discharge.*

*P260 Do not breathe dust/fume/gas/mist/vapors/spray.*

*P264 Wash thoroughly after handling.*

*P270 Do not eat, drink or smoke when using this product.*

*P272 Contaminated work clothing must not be allowed out of the workplace.*

*P280 Wear protective gloves/protective clothing/eye protection/face protection.*

*P284 [In case of inadequate ventilation] wear respiratory protection.*

*P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.*

*P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*P308+P313 IF exposed or concerned: Get medical advice/attention.*

*P321 Specific treatment (see on this label).*

*P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*

*P337+P313 If eye irritation persists: Get medical advice/attention.*

*P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.*

*P362+P364 Take off contaminated clothing and wash it before reuse.*

*P363 Wash contaminated clothing before reuse.*

*P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*P403+P235 Store in a well-ventilated place. Keep cool.*

*P405 Store locked up.*

*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 2)

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

123-86-4	n-butyl acetate	13 - 30%
67-64-1	acetone	13 - 30%
112-07-2	2-butoxyethyl acetate	7 - 10%
28182-81-2	HDI Prepolymer	7 - 10%
108-65-6	2-methoxy-1-methylethyl acetate	5 - 7%
112926-00-8	precipitated Silica (Silica-Amorphous)	1.5 - 5%
110-43-0	heptan-2-one	1.5 - 5%
108-83-8	2,6-dimethylheptan-4-one	1.5 - 5%
1330-20-7	xylene	1-1.5%
14807-96-6	Talc	1-1.5%
19549-80-5	4,6-dimethylheptan-2-one	1-1.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	1-1.5%
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate	≤1%

### 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 3)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

123-86-4	n-butyl acetate	5 ppm
67-64-1	acetone	200 ppm
112-07-2	2-butoxyethyl acetate	15 ppm
28182-81-2	HDI Prepolymer	7.8 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
110-43-0	heptan-2-one	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
1330-20-7	xylene	130 ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	150 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	140 ppm
9002-88-4	Polyethylene low density	16 mg/m <sup>3</sup>
108-67-8	mesitylene	140 ppm
25322-68-3	Polyethylene glycol	30 mg/m <sup>3</sup>

(Contd. on page 5)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 4)

98-82-8	cumene	50 ppm
78-83-1	butanol	150 ppm
100-41-4	ethylbenzene	33 ppm

**· PAC-2:**

123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
112-07-2	2-butoxyethyl acetate	35 ppm
28182-81-2	HDI Prepolymer	86 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m3
110-43-0	heptan-2-one	670 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
1330-20-7	xylene	920* ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	350 ppm
1333-86-4	Carbon black	99 mg/m3
95-63-6	1,2,4-trimethylbenzene	360 ppm
9002-88-4	Polyethylene low density	170 mg/m3
108-67-8	mesitylene	360 ppm
25322-68-3	Polyethylene glycol	1,300 mg/m3
98-82-8	cumene	300 ppm
78-83-1	butanol	1,300 ppm
100-41-4	ethylbenzene	1100* ppm

**· PAC-3:**

123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
112-07-2	2-butoxyethyl acetate	210 ppm
28182-81-2	HDI Prepolymer	510 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m3
110-43-0	heptan-2-one	4000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
1330-20-7	xylene	2500* ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	2100* ppm
1333-86-4	Carbon black	590 mg/m3
95-63-6	1,2,4-trimethylbenzene	480 ppm
9002-88-4	Polyethylene low density	1,000 mg/m3
108-67-8	mesitylene	480 ppm
25322-68-3	Polyethylene glycol	7,700 mg/m3
98-82-8	cumene	730 ppm
78-83-1	butanol	8000* ppm

(Contd. on page 6)



**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

100-41-4 ethylbenzene

(Contd. of page 5)

1800\* ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
BEI	

### 112-07-2 2-butoxyethyl acetate

REL	Long-term value: 33 mg/m <sup>3</sup> , 5 ppm
TLV	Long-term value: 130 mg/m <sup>3</sup> , 20 ppm

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

(Contd. on page 7)



**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 6)

**112926-00-8 precipitated Silica (Silica-Amorphous)**

PEL 20mppcf or 80mg/m<sup>3</sup> /%SiO<sub>2</sub>  
REL Long-term value: 6 mg/m<sup>3</sup>  
See Pocket Guide App. C  
TLV TLV withdrawn

**110-43-0 heptan-2-one**

PEL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm  
REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm  
TLV Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

**108-83-8 2,6-dimethylheptan-4-one**

PEL Long-term value: 290 mg/m<sup>3</sup>, 50 ppm  
REL Long-term value: 150 mg/m<sup>3</sup>, 25 ppm  
TLV Long-term value: 145 mg/m<sup>3</sup>, 25 ppm

**1330-20-7 xylene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI

**· Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 8)



**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 7)

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



*Protective gloves*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



*Tightly sealed goggles*

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· **Flash point:** -18 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 280 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.2 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.97 g/cm<sup>3</sup>

· **Relative density** Not determined.

(Contd. on page 9)





**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 8)

· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	61.8 %
<b>VOC content:</b>	43.8 %
	545.2 g/l / 4.55 lb/gl
· <b>Solids content:</b>	45.5 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 28182-81-2 HDI Prepolymer

Oral	LD50	1000 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	LC50/4 h	137-1150 mg/l (rat)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
- Sensitization possible through inhalation.
- Sensitization possible through skin contact.

(Contd. on page 10)



**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 9)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc	3
1333-86-4	Carbon black	2B
9002-88-4	Polyethylene low density	3
98-82-8	cumene	2B
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
---------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.





USA

(Contd. on page 11)

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 10)

## 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, ADR, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Paint
· <b>ADR</b>	1263 Paint, special provision 640D
· <b>IMDG, IATA</b>	PAINT
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>ADR</b>	
 	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>EMS Number:</b>	F-E, <u>S-E</u>
· <b>Stowage Category</b>	B
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

(Contd. on page 12)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 11)

· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

### **15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

	Acrylic Resin
112-07-2	2-butoxyethyl acetate
1330-20-7	xylene
14807-96-6	Talc
95-63-6	1,2,4-trimethylbenzene
98-82-8	cumene
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate
67-64-1	acetone
112-07-2	2-butoxyethyl acetate
28182-81-2	HDI Prepolymer
108-65-6	2-methoxy-1-methylethyl acetate
9004-36-8	Cellulose Acetate Butyrate
110-43-0	heptan-2-one
108-83-8	2,6-dimethylheptan-4-one
1330-20-7	xylene
14807-96-6	Talc
19549-80-5	4,6-dimethylheptan-2-one
64742-95-6	Solvent naphtha (petroleum), light arom.
123-42-2	4-hydroxy-4-methylpentan-2-one
1333-86-4	Carbon black
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny)l sebacate
95-63-6	1,2,4-trimethylbenzene

(Contd. on page 13)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 12)

9002-88-4	Polyethylene low density
104810-48-2	poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy-
104810-47-1	poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-
108-67-8	mesitylene
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
25322-68-3	Polyethylene glycol
9038-95-3	OXIRANE,ME, POLYMER
98-82-8	cumene
106-79-6	Dimethyl sebacate(Impurity)
78-83-1	butanol
100-41-4	ethylbenzene
2403-89-6	4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)

**· Proposition 65**

**· Chemicals known to cause cancer:**

1330-20-7	xylene
1333-86-4	Carbon black
95-63-6	1,2,4-trimethylbenzene
98-82-8	cumene
100-41-4	ethylbenzene

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**· Cancerogenity categories**

**· EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
95-63-6	1,2,4-trimethylbenzene	II
108-67-8	mesitylene	II
98-82-8	cumene	D, CBD
100-41-4	ethylbenzene	D

**· TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
112-07-2	2-butoxyethyl acetate	A3
1330-20-7	xylene	A4
14807-96-6	Talc	A4
1333-86-4	Carbon black	A4

(Contd. on page 14)

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 13)

100-41-4	ethylbenzene	A3
----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02    GHS08    GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

HDI Prepolymer

n-butyl acetate

Solvent naphtha (petroleum), light arom.  
acetone

bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

(Contd. on page 15)

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

(Contd. of page 14)

P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*  
 P337+P313 *If eye irritation persists: Get medical advice/attention.*  
 P342+P311 *If experiencing respiratory symptoms: Call a POISON CENTER/doctor.*  
 P362+P364 *Take off contaminated clothing and wash it before reuse.*  
 P363 *Wash contaminated clothing before reuse.*  
 P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*  
 P403+P235 *Store in a well-ventilated place. Keep cool.*  
 P405 *Store locked up.*  
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**  
*Carcinogenic hazardous material group III (dangerous).*

· **Information about limitation of use:**

*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.*  
*Exceptions can be made by the authorities in certain cases.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** *Environment protection department.*

· **Contact:** *Steve Gaver (sgaver@semproducts.com)*

· **Date of preparation / last revision** *06/28/2017 / 6*

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Resp. Sens. 1: Respiratory sensitisation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Muta. 1B: Germ cell mutagenicity – Category 1B*

(Contd. on page 16)





Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: HR010 Hot Rod Black Kit with HR014,HRC06 & HRR06**

*Carc. 1B: Carcinogenicity – Category 1B*

*STOT SE 2: Specific target organ toxicity (single exposure) – Category 2*

**\* Data compared to the previous version altered.**

(Contd. of page 15)

USA