

1 Identification

- **Product identifier**
- **Trade name:** 64033, 64043, 64063, 64093
- **Article number:** 64033, 64043, 64063, 64093
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1 H360 May damage fertility or the unborn child.

STOT RE 1 H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene
acetone
Solvent naphtha (petroleum), light arom.
Stoddard solvent
2-butanone oxime

· **Hazard statements**

H222 *Extremely flammable aerosol.*
H280 *Contains gas under pressure; may explode if heated.*
H315 *Causes skin irritation.*
H319 *Causes serious eye irritation.*
H317 *May cause an allergic skin reaction.*
H340 *May cause genetic defects.*
H350 *May cause cancer.*
H360 *May damage fertility or the unborn child.*
H336 *May cause drowsiness or dizziness.*
H372-H373 *Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.*
H304 *May be fatal if swallowed and enters airways.*

· **Precautionary statements**

P201 *Obtain special instructions before use.*
P202 *Do not handle until all safety precautions have been read and understood.*
P210 *Keep away from heat/sparks/open flames/hot surfaces. No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Do not pierce or burn, even after use.*
P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
P264 *Wash thoroughly after handling.*
P270 *Do not eat, drink or smoke when using this product.*
P271 *Use only outdoors or in a well-ventilated area.*
P272 *Contaminated work clothing must not be allowed out of the workplace.*
P280 *Wear protective gloves/protective clothing/eye protection/face protection.*
P301+P310 *IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*
P302+P352 *IF ON SKIN: Wash with plenty of water.*
P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P308+P313 *IF exposed or concerned: Get medical advice/attention.*
P312 *Call a POISON CENTER/doctor if you feel unwell.*
P314 *Get medical advice/attention if you feel unwell.*
P321 *Specific treatment (see on this label).*
P331 *Do NOT induce vomiting.*
P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*
P337+P313 *If eye irritation persists: Get medical advice/attention.*
P362+P364 *Take off contaminated clothing and wash it before reuse.*

(Contd. on page 3)



Trade name: 64033, 64043, 64063, 64093

(Contd. of page 2)

P363 Wash contaminated clothing before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**

Health = *1

Fire = 4

Reactivity = 3

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

67-64-1	acetone	13 - 30%
74-98-6	propane	13 - 30%
123-86-4	n-butyl acetate	13 - 30%
108-88-3	toluene	10 - 13%
	Alkyd Resin	10 - 13%
763-69-9	ethyl 3-ethoxypropionate	1.5 - 5%
78-93-3	butanone	1.5 - 5%
107-87-9	pentan-2-one	1.5 - 5%
64742-95-6	Solvent naphtha (petroleum), light arom.	1.5 - 5%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	1-1.5%
8052-41-3	Stoddard solvent	≤1%
84-74-2	dibutyl phthalate	≤1%
108-10-1	4-methylpentan-2-one	≤1%

USA

(Contd. on page 4)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 3)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-64-1	acetone	200 ppm
74-98-6	propane	5500* ppm
123-86-4	n-butyl acetate	5 ppm
108-88-3	toluene	67 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
78-93-3	butanone	200 ppm
107-87-9	pentan-2-one	150 ppm
1333-86-4	Carbon black	9 mg/m ³
8052-41-3	Stoddard solvent	300 mg/m ³

(Contd. on page 5)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 4)

95-63-6	1,2,4-trimethylbenzene	140 ppm
84-74-2	dibutyl phthalate	15 mg/m3
108-67-8	mesitylene	140 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
108-10-1	4-methylpentan-2-one	75 ppm
1330-20-7	xylene	130 ppm
111-76-2	2-butoxyethanol	60 ppm
96-29-7	2-butanone oxime	30 ppm
98-82-8	cumene	50 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	3.4 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m3
107-98-2	1-methoxy-2-propanol	100 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

· PAC-2:

67-64-1	acetone	3200* ppm
74-98-6	propane	17000** ppm
123-86-4	n-butyl acetate	200 ppm
108-88-3	toluene	560 ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
78-93-3	butanone	2700* ppm
107-87-9	pentan-2-one	830 ppm
1333-86-4	Carbon black	99 mg/m3
8052-41-3	Stoddard solvent	1,800 mg/m3
95-63-6	1,2,4-trimethylbenzene	360 ppm
84-74-2	dibutyl phthalate	1,600 mg/m3
108-67-8	mesitylene	360 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
108-10-1	4-methylpentan-2-one	500 ppm
1330-20-7	xylene	920* ppm
111-76-2	2-butoxyethanol	120 ppm
96-29-7	2-butanone oxime	56 ppm
98-82-8	cumene	300 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
111-77-3	2-(2-methoxyethoxy)ethanol	37 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m3
107-98-2	1-methoxy-2-propanol	160 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

(Contd. on page 6)



Trade name: 64033, 64043, 64063, 64093

(Contd. of page 5)

· PAC-3:		
67-64-1	acetone	5700* ppm
74-98-6	propane	33000*** ppm
123-86-4	n-butyl acetate	3000* ppm
108-88-3	toluene	3700* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
78-93-3	butanone	4000* ppm
107-87-9	pentan-2-one	5000* ppm
1333-86-4	Carbon black	590 mg/m3
8052-41-3	Stoddard solvent	29500** mg/m3
95-63-6	1,2,4-trimethylbenzene	480 ppm
84-74-2	dibutyl phthalate	9300* mg/m3
108-67-8	mesitylene	480 ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
1330-20-7	xylene	2500* ppm
111-76-2	2-butoxyethanol	700 ppm
96-29-7	2-butanone oxime	250 ppm
98-82-8	cumene	730 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
111-77-3	2-(2-methoxyethoxy)ethanol	220 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m3
107-98-2	1-methoxy-2-propanol	660 ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 7)

USA



Trade name: 64033, 64043, 64063, 64093

(Contd. of page 6)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
BEI	

74-98-6 propane

PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; D, EX

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm
	Long-term value: 238 mg/m ³ , 50 ppm

108-88-3 toluene

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm
BEI	

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm
	Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm
	Long-term value: 590 mg/m ³ , 200 ppm
BEI	

107-87-9 pentan-2-one

PEL	Long-term value: 700 mg/m ³ , 200 ppm
REL	Long-term value: 530 mg/m ³ , 150 ppm
TLV	Short-term value: 529 mg/m ³ , 150 ppm

(Contd. on page 8)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 7)

8052-41-3 Stoddard solvent

PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 mg/m³
Ceiling limit value: 1800* mg/m³
*15-min

TLV Long-term value: 525 mg/m³, 100 ppm

84-74-2 dibutyl phthalate

PEL Long-term value: 5 mg/m³

REL Long-term value: 5 mg/m³

TLV Long-term value: 5 mg/m³

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm

REL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 307 mg/m³, 75 ppm
Long-term value: 82 mg/m³, 20 ppm
BEI

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: MEK

108-10-1 4-methylpentan-2-one

(Contd. on page 9)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 8)

BEI 1 mg/L
Medium: urine
Time: end of shift
Parameter: MIBK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

(Contd. on page 10)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 9)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C
· Flash point:	-97 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C:	8300 hPa
· Density at 20 °C:	0.76838 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	86.1 %
VOC content:	64.7 %
	628.3 g/l / 5.24 lb/gal
Solids content:	14.2 %
· Other information	No further relevant information available.

*

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 11)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 10)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

84-74-2 dibutyl phthalate

Oral	LD50	8000 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1333-86-4	Carbon black	2B
108-10-1	4-methylpentan-2-one	2B
	BENTONITE	suspected carcinogen <2% 14808-60-7
1330-20-7	xylene	3
111-76-2	2-butoxyethanol	3
98-82-8	cumene	2B
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
---------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

(Contd. on page 12)



Trade name: 64033, 64043, 64063, 64093

(Contd. of page 11)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · DOT | Aerosols, flammable |
| · ADR | 1950 Aerosols |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

- **Transport hazard class(es)**

- **DOT**



- | | |
|----------------|-----|
| · Class | 2.1 |
| · Label | 2.1 |

- **ADR**



- | | |
|----------------|------------|
| · Class | 2 5F Gases |
|----------------|------------|

(Contd. on page 13)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 12)

· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1

· **Label** 2.1

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Gases

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **Remarks**

ORM-D 49CFR 173-150,156,306

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

USA

(Contd. on page 14)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 13)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3	toluene
78-93-3	butanone
95-63-6	1,2,4-trimethylbenzene
84-74-2	dibutyl phthalate
108-10-1	4-methylpentan-2-one
1330-20-7	xylene
111-76-2	2-butoxyethanol
98-82-8	cumene
	COBALT CARBOXYLATE
100-41-4	ethylbenzene
111-77-3	2-(2-methoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
74-98-6	propane
123-86-4	n-butyl acetate
108-88-3	toluene
763-69-9	ethyl 3-ethoxypropionate
78-93-3	butanone
107-87-9	pentan-2-one
64742-95-6	Solvent naphtha (petroleum), light arom.
64742-88-7	Solvent naphtha (petroleum), medium aliph.
1333-86-4	Carbon black
8052-41-3	Stoddard solvent
95-63-6	1,2,4-trimethylbenzene
84-74-2	dibutyl phthalate
108-67-8	mesitylene
108-83-8	2,6-dimethylheptan-4-one
108-10-1	4-methylpentan-2-one
1330-20-7	xylene
111-76-2	2-butoxyethanol
96-29-7	2-butanone oxime
9038-95-3	OXIRANE,ME, POLYMER
138-86-3	dipentene
98-82-8	cumene
97-64-3	ethyl lactate

(Contd. on page 15)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 14)

7397-62-8	butyl glycollate
108-65-6	2-methoxy-1-methylethyl acetate
15956-58-8	Manganese 2-Ethylhexanoate
100-41-4	ethylbenzene
111-77-3	2-(2-methoxyethoxy)ethanol
149-57-5	2-ethylhexanoic acid
107-98-2	1-methoxy-2-propanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
95-63-6	1,2,4-trimethylbenzene
108-10-1	4-methylpentan-2-one
1330-20-7	xylene
98-82-8	cumene
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

84-74-2	dibutyl phthalate
---------	-------------------

· **Chemicals known to cause reproductive toxicity for males:**

84-74-2	dibutyl phthalate
---------	-------------------

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
84-74-2	dibutyl phthalate
108-10-1	4-methylpentan-2-one

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
78-93-3	butanone	I
95-63-6	1,2,4-trimethylbenzene	II
84-74-2	dibutyl phthalate	D
108-67-8	mesitylene	II
108-10-1	4-methylpentan-2-one	I
1330-20-7	xylene	I
111-76-2	2-butoxyethanol	NL
98-82-8	cumene	D, CBD
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4

(Contd. on page 16)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 15)

111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene

acetone

Solvent naphtha (petroleum), light arom.

Stoddard solvent

2-butanone oxime

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

(Contd. on page 17)

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 16)

P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/28/2017 / 12

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

(Contd. on page 18)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 64033, 64043, 64063, 64093

(Contd. of page 17)

Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Compressed gas
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1: Reproductive toxicity – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

USA