

1 Identification

- **Product identifier**
- **Trade name:** 39847 Multi-Plastic Repair Material
- **Article number:** 39847
- **Application of the substance / the mixture** Adhesives
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard-determining components of labeling:**
bisphenolA(chloro)oxirane polymer
Talc
2,4,6-tris(dimethylaminomethyl)phenol
Mercaptan Terminated Polymer NJTS 800938 5952
ELASTOMER MODIFIED DIGLYCIDAL ETHER
CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER
- **Hazard statements**
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

(Contd. on page 2)

USA

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 1)

H335 May cause respiratory irritation.

· **Precautionary statements**

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves / eye protection / face protection.
- P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321 Specific treatment (see on this label).
- P330 Rinse mouth.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

	Talc	30 - 40%
	Mercaptan Terminated Polymer NJTS 800938 5952	13 - 30%
25068-38-6	bisphenolA(chloro)oxirane polymer	13 - 30%

(Contd. on page 3)



Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 2)

65997-17-3	Glass	5 - 7%
26142-30-3	Epoxy Resin	5 - 7%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER	1-1.5%
14228-73-0	CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER	≤1%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Immediately call a doctor.

- **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-I:**

25068-38-6	bisphenolA(chloro)oxirane polymer	90 mg/m3
65997-17-3	Glass	15 mg/m3

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 3)

90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m ³
13463-67-7	titanium dioxide	30 mg/m ³
919-30-2	3-aminopropyltriethoxysilane	1.9 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
57-11-4	stearic acid, pure	14 mg/m ³
67762-90-7	FUMED SILICA	120 mg/m ³
280-57-9	triethylenediamine	5.1 mg/m ³
107-21-1	ethanediol	30 ppm
1333-86-4	Carbon black	9 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
64-17-5	ethanol	1,800 ppm
67-56-1	methanol	530 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
21645-51-2	aluminium hydroxide	8.7 mg/m ³

· PAC-2:

25068-38-6	bisphenolA(chloro)oxirane polymer	990 mg/m ³
65997-17-3	Glass	170 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m ³
13463-67-7	titanium dioxide	330 mg/m ³
919-30-2	3-aminopropyltriethoxysilane	21 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
57-11-4	stearic acid, pure	150 mg/m ³
67762-90-7	FUMED SILICA	1,300 mg/m ³
280-57-9	triethylenediamine	56 mg/m ³
107-21-1	ethanediol	150 ppm
1333-86-4	Carbon black	99 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
64-17-5	ethanol	3300* ppm
67-56-1	methanol	2,100 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
21645-51-2	aluminium hydroxide	73 mg/m ³

· PAC-3:

25068-38-6	bisphenolA(chloro)oxirane polymer	5,900 mg/m ³
65997-17-3	Glass	990 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m ³
919-30-2	3-aminopropyltriethoxysilane	350 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
57-11-4	stearic acid, pure	910 mg/m ³
67762-90-7	FUMED SILICA	7,900 mg/m ³
280-57-9	triethylenediamine	340 mg/m ³

(Contd. on page 5)

USA

Trade name: 39847 Multi-Plastic Repair Material

		(Contd. of page 4)
107-21-1	ethanediol	900 ppm
1333-86-4	Carbon black	590 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
64-17-5	ethanol	15000* ppm
67-56-1	methanol	7200* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
21645-51-2	aluminium hydroxide	440 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 5)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	201 °C

· **Flash point:** 257 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.
In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure:** Not determined.

Density at 20 °C:	1.59895 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

· **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.

(Contd. on page 7)


Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 6)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 0.0 %
- **Solids content:** 99.9 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

	Talc	3
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO ₂)	1
64-17-5	ethanol	1
7631-86-9	silicon dioxide, chemically prepared	3

· NTP (National Toxicology Program)

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

(Contd. on page 8)

USA



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **Persistence and degradability** *No further relevant information available.*
- **Behavior in environmental systems:**
- **Bioaccumulative potential** *No further relevant information available.*
- **Mobility in soil** *No further relevant information available.*
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **Other adverse effects** *No further relevant information available.*

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

- | | |
|---------------------------------------|------------------------|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | <i>Void</i> |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | <i>Void</i> |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | <i>Void</i> |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | <i>Void</i> |
| · Environmental hazards: | |
| · Marine pollutant: | <i>No</i> |
| · Special precautions for user | <i>Not applicable.</i> |

(Contd. on page 9)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 8)

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Remarks** NOT REGULATED
- **UN "Model Regulation":** Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

	Talc
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER
107-21-1	ethanediol
67-56-1	methanol

· **TSCA (Toxic Substances Control Act):**

	Talc
25068-38-6	bisphenolA(chloro)oxirane polymer
1317-65-3	GROUND CALCIUM CARBONATE
65997-17-3	Glass
26142-30-3	Epoxy Resin
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol
13463-67-7	titanium dioxide
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate
14228-73-0	CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER
919-30-2	3-aminopropyltriethoxysilane
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
57-11-4	stearic acid, pure
67762-90-7	FUMED SILICA
280-57-9	triethylenediamine
107-21-1	ethanediol
1333-86-4	Carbon black
14808-60-7	Quartz (SiO2)
64-17-5	ethanol
67-56-1	methanol
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide

(Contd. on page 10)

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 9)

7732-18-5	water
-----------	-------

· **Proposition 65**

· **Chemicals known to cause cancer:**

25068-38-6	bisphenolA(chloro)oxirane polymer
13463-67-7	titanium dioxide
163440-98-0	ELASTOMER MODIFIED DIGLYCIDAL ETHER
107-21-1	ethanediol
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

107-21-1	ethanediol
64-17-5	ethanol
67-56-1	methanol

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

	Talc	A4
13463-67-7	titanium dioxide	A4
107-21-1	ethanediol	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO ₂)	A2
64-17-5	ethanol	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

bisphenolA(chloro)oxirane polymer
Talc

(Contd. on page 11)



Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 10)

2,4,6-tris(dimethylaminomethyl)phenol
Mercaptan Terminated Polymer NJTS 800938 5952
ELASTOMER MODIFIED DIGLYCIDAL ETHER
CYCLOHEXANEDIMETHANOL DIGLYCIDAL ETHER

· **Hazard statements**

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves / eye protection / face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P330 Rinse mouth.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/28/2017 / 6

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39847 Multi-Plastic Repair Material

(Contd. of page 11)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

USA