

1 Identification

- **Product identifier**
- **Trade name:** 39537 Weld Bond Adhesive
- **Article number:** 39537
- **Application of the substance / the mixture** Assembly adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS05



GHS07



GHS08

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

methyl methacrylate
PHOSPHATE ESTER OF 2-HYDROXYETHYL METHACRYLATE
ACRYLONITRILE/BUTADIENE RESIN
2-hydroxyethyl methacrylate
n-butyl methacrylate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.

· **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

(Contd. on page 3)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

80-62-6	methyl methacrylate	40 - 60%
9003-56-9	ACRYLONITRILE/BUTADIENE RESIN	13 - 30%
868-77-9	2-hydroxyethyl methacrylate	1.5 - 5%
97-88-1	n-butyl methacrylate	1.5 - 5%
7646-85-7	zinc chloride	1-1.5%
79-41-4	methacrylic acid	1-1.5%
52628-03-2	PHOSPHATE ESTER OF 2-HYDROXYETHYL METHACRYLATE	1-1.5%
27138-31-4	BENZOIC ACID ESTER	1-1.5%
56-23-5	carbon tetrachloride	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Trade name: 39537 Weld Bond Adhesive

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

80-62-6	methyl methacrylate	17 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m3
97-88-1	n-butyl methacrylate	19 mg/m3
7646-85-7	zinc chloride	2 mg/m3
79-41-4	methacrylic acid	6.7 ppm
56-23-5	carbon tetrachloride	1.2 ppm
1333-86-4	Carbon black	9 mg/m3

· PAC-2:

80-62-6	methyl methacrylate	120 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m3
97-88-1	n-butyl methacrylate	210 mg/m3
7646-85-7	zinc chloride	800 mg/m3
79-41-4	methacrylic acid	61 ppm
56-23-5	carbon tetrachloride	13 ppm
1333-86-4	Carbon black	99 mg/m3

· PAC-3:

80-62-6	methyl methacrylate	570 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m3
97-88-1	n-butyl methacrylate	1,300 mg/m3
7646-85-7	zinc chloride	4,800 mg/m3
79-41-4	methacrylic acid	220 ppm
56-23-5	carbon tetrachloride	340 ppm

(Contd. on page 5)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive

1333-86-4 Carbon black

(Contd. of page 4)

590 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 410 mg/m ³ , 100 ppm
	Long-term value: 205 mg/m ³ , 50 ppm
	DSEN

7646-85-7 zinc chloride

PEL	Long-term value: 1 mg/m ³
	Fume
REL	Short-term value: 2 mg/m ³
	Long-term value: 1 mg/m ³
TLV	Short-term value: 2 mg/m ³
	Long-term value: 1 mg/m ³
	fume

79-41-4 methacrylic acid

REL	Long-term value: 70 mg/m ³ , 20 ppm
	Skin
TLV	Long-term value: 70 mg/m ³ , 20 ppm

(Contd. on page 6)

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 5)

56-23-5 carbon tetrachloride

PEL	Long-term value: 10 ppm Ceiling limit value: 25; 200* ppm *5-min peak in any 4 hrs
REL	Short-term value: 12.6* mg/m ³ , 2* ppm *60-min; See Pocket Guide App. A
TLV	Short-term value: 63 mg/m ³ , 10 ppm Long-term value: 31 mg/m ³ , 5 ppm Skin

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 6)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	101 °C
· Flash point:	10 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C:	47 hPa
· Density at 20 °C:	0.98506 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	
Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.1 %
VOC content:	0.1 %
Solids content:	96.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

(Contd. on page 8)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 7)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

80-62-6 methyl methacrylate

Oral	LD50	7872 mg/kg (rat)
------	------	------------------

7646-85-7 zinc chloride

Oral	LD50	350 mg/kg (rat)
------	------	-----------------

56-23-5 carbon tetrachloride

Oral	LD50	2350 mg/kg (rat)
------	------	------------------

Dermal	LD50	5070 mg/kg (rat)
--------	------	------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

80-62-6	methyl methacrylate	3
56-23-5	carbon tetrachloride	2B
1333-86-4	Carbon black	2B

- **NTP (National Toxicology Program)**

56-23-5	carbon tetrachloride	R
---------	----------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 9)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive



(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1133
- **UN proper shipping name**
- **DOT** Adhesives
- **ADR** 1133 Adhesives, special provision 640D
- **IMDG, IATA** ADHESIVES
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II

(Contd. on page 10)

USA



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 9)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E,S-D
· Segregation groups	Acids, liquid halogenated hydrocarbons
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6	methyl methacrylate
7646-85-7	zinc chloride
56-23-5	carbon tetrachloride

· TSCA (Toxic Substances Control Act):

80-62-6	methyl methacrylate
9003-56-9	ACRYLONITRILE/BUTADIENE RESIN
868-77-9	2-hydroxyethyl methacrylate
97-88-1	n-butyl methacrylate
7646-85-7	zinc chloride
120-56-9	TRIETHYLENEGLYCOL DIBENZOATE
79-41-4	methacrylic acid
52628-03-2	PHOSPHATE ESTER OF 2-HYDROXYETHYL METHACRYLATE

(Contd. on page 11)

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 10)

27138-31-4	BENZOIC ACID ESTER
56-23-5	carbon tetrachloride
1333-86-4	Carbon black

· **Proposition 65**

· **Chemicals known to cause cancer:**

9003-56-9	ACRYLONITRILE/BUTADIENE RESIN
56-23-5	carbon tetrachloride
1333-86-4	Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

80-62-6	methyl methacrylate	E, NL
7646-85-7	zinc chloride	D, I, II
56-23-5	carbon tetrachloride	L

· **TLV (Threshold Limit Value established by ACGIH)**

80-62-6	methyl methacrylate	A4
56-23-5	carbon tetrachloride	A2
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

56-23-5	carbon tetrachloride
1333-86-4	Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

methyl methacrylate
PHOSPHATE ESTER OF 2-HYDROXYETHYL METHACRYLATE
ACRYLONITRILE/BUTADIENE RESIN
2-hydroxyethyl methacrylate
n-butyl methacrylate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.

(Contd. on page 12)

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 11)

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/28/2017 / 7

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 13)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39537 Weld Bond Adhesive

(Contd. of page 12)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**

USA