

## 1 Identification

- **Product identifier**
- **Trade name:** 39757 Dual Mix Structural Impact Repair Adhesive
- **Article number:** 39757
- **Application of the substance / the mixture** Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

POLYOXYPROPYLENEDIAMINE

Poly(oxy-1,4-butanediyl), a-hydro-w-hydroxy-, polymer with ammonia

(Contd. on page 2)



## Trade name: 39757 Dual Mix Structural Impact Repair Adhesive

(Contd. of page 1)

bisphenolA(chloro)oxirane polymer

POLYAMINOAMIDE

1,4-bis(2,3-epoxypropoxy)butane

TERTIARY AMINE

3-aminopropyldimethylamine

3,6-diazaoctanethylenediamin

· **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· **Precautionary statements**

P260 Do not breathe dusts or mists.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 3

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = \*3

Fire = 1

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.

(Contd. on page 3)

USA

**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**

(Contd. of page 2)

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

|             |  |          |
|-------------|--|----------|
| 25068-38-6  | bisphenolA(chloro)oxirane polymer                                  | 13 - 30% |
| 14807-96-6  | Talc   | 13 - 30% |
| 960525-56-8 | Poly(oxy-1,4-butanediyl), a-hydro-w-hydroxy-, polymer with ammonia | 10 - 13% |
| 1761-71-3   | 4,4'-methylenebis(cyclohexylamine)                                 | 10 - 13% |
| 2425-79-8   | 1,4-bis(2,3-epoxypropoxy)butane                                    | 7 - 10%  |
| 9046-10-0   | POLYOXYPROPYLENEDIAMINE  | 7 - 10%  |
| 68410-23-1  | POLYAMINOAMIDE   | 7 - 10%  |
| 52338-87-1  | TERTIARY AMINE   | 1.5 - 5% |
| 109-55-7    | 3-aminopropyldimethylamine   | 1.5 - 5% |
| 112-24-3    | 3,6-diazaoctanethylenediamin                                       | ≤1%      |

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

|            |                                   |           |
|------------|-----------------------------------|-----------|
| 25068-38-6 | bisphenolA(chloro)oxirane polymer | 90 mg/m3  |
| 2425-79-8  | 1,4-bis(2,3-epoxypropoxy)butane   | 16 mg/m3  |
| 9046-10-0  | POLYOXYPROPYLENEDIAMINE           | 4.8 mg/m3 |
| 68410-23-1 | POLYAMINOAMIDE                    | 30 mg/m3  |
| 109-55-7   | 3-aminopropyl dimethylamine       | 1.2 ppm   |
| 112-24-3   | 3,6-diazaoctanethylenediamin      | 3 ppm     |

### · PAC-2:

|            |                                   |           |
|------------|-----------------------------------|-----------|
| 25068-38-6 | bisphenolA(chloro)oxirane polymer | 990 mg/m3 |
| 2425-79-8  | 1,4-bis(2,3-epoxypropoxy)butane   | 170 mg/m3 |
| 9046-10-0  | POLYOXYPROPYLENEDIAMINE           | 53 mg/m3  |
| 68410-23-1 | POLYAMINOAMIDE                    | 330 mg/m3 |
| 109-55-7   | 3-aminopropyl dimethylamine       | 13 ppm    |
| 112-24-3   | 3,6-diazaoctanethylenediamin      | 14 ppm    |

### · PAC-3:

|            |                                   |             |
|------------|-----------------------------------|-------------|
| 25068-38-6 | bisphenolA(chloro)oxirane polymer | 5,900 mg/m3 |
| 2425-79-8  | 1,4-bis(2,3-epoxypropoxy)butane   | 220 mg/m3   |
| 9046-10-0  | POLYOXYPROPYLENEDIAMINE           | 320 mg/m3   |
| 68410-23-1 | POLYAMINOAMIDE                    | 2,000 mg/m3 |
| 109-55-7   | 3-aminopropyl dimethylamine       | 89 ppm      |
| 112-24-3   | 3,6-diazaoctanethylenediamin      | 83 ppm      |

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.

(Contd. on page 5)

**Trade name:** 39757 Dual Mix Structural Impact Repair Adhesive

(Contd. of page 4)

Ensure good ventilation/exhaustion at the workplace.

- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 112-24-3 3,6-diazaoctanethylenediamin

|      |  |
|------|--|
| WEEL | Long-term value: 6 mg/m <sup>3</sup> , 1 ppm |
|      | Skin   |

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)


**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

|                 |                                    |
|-----------------|------------------------------------|
| Form:           | Liquid                             |
| Color:          | According to product specification |
| Odor:           | Characteristic                     |
| Odor threshold: | Not determined.                    |

· **pH-value:** Not determined.· **Change in condition**

|                              |               |
|------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | >260 °C       |

· **Flash point:** 200 °C· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 595 °C· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.
 · **Danger of explosion:** Product does not present an explosion hazard.  
 In use, may form flammable/explosive vapour-air mixture.
· **Explosion limits:**

|        |                 |
|--------|-----------------|
| Lower: | Not determined. |
| Upper: | Not determined. |

· **Vapor pressure:** Not determined.· **Density at 20 °C:** 1.14569 g/cm<sup>3</sup>· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

|            |                 |
|------------|-----------------|
| Dynamic:   | Not determined. |
| Kinematic: | Not determined. |

· **Solvent content:**

Organic solvents: 0.0 %

(Contd. on page 7)



Printing date 06/28/2017

Reviewed on 06/28/2017

**Trade name:** 39757 Dual Mix Structural Impact Repair Adhesive

(Contd. of page 6)

|                          |  |
|--------------------------|--|
| <b>Solids content:</b>   | 87.6 %                                     |
| <b>Other information</b> | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**  
Strong caustic effect.  
Strong irritant with the danger of severe eye injury.
- **Sensitization:**  
Sensitization possible through inhalation.  
Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|                 |   |
|-----------------|---|
| 14807-96-6 Talc | 3 |
|-----------------|---|

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)



**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**


(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Must not reach bodies of water or drainage ditch undiluted or unneutralized.*  
*Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |   |
|---|---|
| · <b>UN-Number</b>  | UN1760  |
| · <b>DOT, ADR, IMDG, IATA</b>   |   |
| · <b>UN proper shipping name</b>  | Corrosive liquids, n.o.s. (POLYOXYPROPYLENEDIAMINE, 3-aminopropyldimethylamine)   |
| · <b>DOT</b>  | 1760 Corrosive liquids, n.o.s. (POLYOXYPROPYLENEDIAMINE, 3-aminopropyldimethylamine), MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS |
| · <b>ADR</b>  | CORROSIVE LIQUID, N.O.S. (POLYOXYPROPYLENEDIAMINE, 3-aminopropyldimethylamine)  |
| · <b>IMDG, IATA</b>   |   |
| · <b>Transport hazard class(es)</b>   |   |
| · <b>DOT</b>  |   |
|  |   |
| · <b>Class</b>  | 8 Corrosive substances  |
| · <b>Label</b>  | 8   |

(Contd. on page 9)




**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**

(Contd. of page 8)

**· ADR, IMDG**


· **Class** 8 Corrosive substances  
 · **Label** 8

**· IATA**


· **Class** 8 Corrosive substances  
 · **Label** 8

**· Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Product contains environmentally hazardous substances:  
 bisphenolA(chloro)oxirane polymer  
 · **Marine pollutant:** Symbol (fish and tree)  
 · **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Corrosive substances  
 · **EMS Number:** F-A,S-B  
 · **Segregation groups** Alkalies  
 · **Stowage Category** A  
 · **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

**· Transport/Additional information:**

· **DOT**  
 · **Quantity limitations** On passenger aircraft/rail: 5 L  
 On cargo aircraft only: 60 L

**· ADR**

· **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

**· IMDG**

· **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

USA

Trade name: 39757 Dual Mix Structural Impact Repair Adhesive

(Contd. of page 9)

· UN "Model Regulation": UN 1760 CORROSIVE LIQUIDS, N.O.S. (POLYOXYPROPYLENEDIAMINE, 3-AMINOPROPYLDIMETHYLAMINE), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):

14807-96-6 Talc

- TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65

- Chemicals known to cause cancer:

25068-38-6 bisphenolA(chloro)oxirane polymer

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Cancerogenity categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

14807-96-6 Talc

A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS05 GHS07 GHS08

- Signal word Danger

- Hazard-determining components of labeling:

POLYOXYPROPYLENEDIAMINE

Poly(oxy-1,4-butanediyl), α-hydroxy-, polymer with ammonia

bisphenolA(chloro)oxirane polymer

(Contd. on page 11)

**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**

(Contd. of page 10)

**POLYAMINOAMIDE**

1,4-bis(2,3-epoxypropoxy)butane

**TERTIARY AMINE**

3-aminopropyldimethylamine

3,6-diazaoctanethylenediamin

· **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· **Precautionary statements**

P260 Do not breathe dusts or mists.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/28/2017 / 10

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)



Printing date 06/28/2017

Reviewed on 06/28/2017

**Trade name: 39757 Dual Mix Structural Impact Repair Adhesive**

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**

USA