

1 Identification

- **Product identifier**
- **Trade name:** 77713 Urethane Bumper Stripper
- **Article number:** 77713
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS04

GHS07

GHS08

- **Signal word** Danger

(Contd. on page 2)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 1)

· **Hazard-determining components of labeling:**

dichloromethane

Solvent naphtha (petroleum), light aliph.

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H340 May cause genetic defects.

H350 May cause cancer.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P330 Rinse mouth.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 4

Reactivity = 3

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

75-09-2	dichloromethane	70 - 100%
---------	-----------------	-----------

(Contd. on page 3)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 2)

68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
67-63-0	propan-2-ol	7 - 10%
64742-89-8	Solvent naphtha (petroleum), light aliph.	1.5 - 5%
102-71-6	2,2',2''-nitrilotriethanol	≤1%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-I:**

75-09-2	dichloromethane	200 ppm
67-63-0	propan-2-ol	400 ppm
102-71-6	2,2',2''-nitrilotriethanol	15 mg/m ³

(Contd. on page 4)



Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 3)

· **PAC-2:**

75-09-2	dichloromethane	560 ppm
67-63-0	propan-2-ol	2000* ppm
102-71-6	2,2',2''-nitrilotriethanol	240 mg/m ³

· **PAC-3:**

75-09-2	dichloromethane	6,900 ppm
67-63-0	propan-2-ol	12000** ppm
102-71-6	2,2',2''-nitrilotriethanol	1,500 mg/m ³

* **7 Handling and storage**· **Handling:**· **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Keep receptacle tightly sealed.· **Specific end use(s)** No further relevant information available.* **8 Exposure controls/personal protection**· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

75-09-2 dichloromethane

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m ³ , 50 ppm BEI

(Contd. on page 5)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 4)

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

102-71-6 2,2',2''-nitrilotriethanol

TLV	Long-term value: 5 mg/m ³
-----	--------------------------------------

· Ingredients with biological limit values:

75-09-2 dichloromethane

BEI	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
-----	---

67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 5)

· **Eye protection:**

Safety glasses



Tightly sealed goggles

* **9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	40 °C

· **Flash point:** -103 °C· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 425 °C· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.· **Explosion limits:**

Lower:	1.9 Vol %
Upper:	22.0 Vol %

· **Vapor pressure at 20 °C:** 453 hPa

Density at 20 °C:	1.0008 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:**

Organic solvents: 100.0 %

(Contd. on page 7)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 6)

VOC content: 28.0 %
611.6 g/l / 5.10 lb/gl
· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

75-09-2 dichloromethane

Oral	LD50	1600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

75-09-2	dichloromethane	2A
67-63-0	propan-2-ol	3
102-71-6	2,2',2''-nitritotriethanol	3

· **NTP (National Toxicology Program)**

75-09-2	dichloromethane	R
---------	-----------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2	dichloromethane
---------	-----------------

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 - Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1

- **ADR**



- **Class** 2 5F Gases

(Contd. on page 9)

USA

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 8)

· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1

· **Label** 2.1

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Gases

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

USA

(Contd. on page 10)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 9)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

75-09-2 dichloromethane

67-63-0 propan-2-ol

· **TSCA (Toxic Substances Control Act):**

75-09-2 dichloromethane

67-63-0 propan-2-ol

64742-89-8 Solvent naphtha (petroleum), light aliph.

102-71-6 2,2',2''-nitritoltriethanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

75-09-2 dichloromethane

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

75-09-2 dichloromethane

L

· **TLV (Threshold Limit Value established by ACGIH)**

75-09-2 dichloromethane

A3

67-63-0 propan-2-ol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

75-09-2 dichloromethane

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS04

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

dichloromethane

Solvent naphtha (petroleum), light aliph.

· **Hazard statements**

H222 Extremely flammable aerosol.

(Contd. on page 11)

USA

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 10)

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H340 May cause genetic defects.

H350 May cause cancer.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P330 Rinse mouth.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/28/2017 / 10

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 12)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 11)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
· *** Data compared to the previous version altered.**

USA