

1 Identification

- **Product identifier**
- **Trade name:** 39967 Pillar Foam
- **Article number:** 39967
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomers and homologues

4,4'-methylenediphenyl diisocyanate

Acrylic Polyol

(Contd. on page 2)

USA

Trade name: 39967 Pillar Foam

(Contd. of page 1)

methylenediphenyl diisocyanate

· **Hazard statements**

- H332 Harmful if inhaled.*
- H315 Causes skin irritation.*
- H319 Causes serious eye irritation.*
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
- H317 May cause an allergic skin reaction.*
- H351 Suspected of causing cancer.*
- H335 May cause respiratory irritation.*
- H373 May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

- P201 Obtain special instructions before use.*
- P202 Do not handle until all safety precautions have been read and understood.*
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.*
- P264 Wash thoroughly after handling.*
- P271 Use only outdoors or in a well-ventilated area.*
- P272 Contaminated work clothing must not be allowed out of the workplace.*
- P280 Wear protective gloves/protective clothing/eye protection/face protection.*
- P284 [In case of inadequate ventilation] wear respiratory protection.*
- P302+P352 IF ON SKIN: Wash with plenty of water.*
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P308+P313 IF exposed or concerned: Get medical advice/attention.*
- P312 Call a POISON CENTER/doctor if you feel unwell.*
- P314 Get medical advice/attention if you feel unwell.*
- P321 Specific treatment (see on this label).*
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*
- P337+P313 If eye irritation persists: Get medical advice/attention.*
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.*
- P362+P364 Take off contaminated clothing and wash it before reuse.*
- P363 Wash contaminated clothing before reuse.*
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.*
- P405 Store locked up.*
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39967 Pillar Foam

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

	Acrylic Polyol	40 - 60%
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	13 - 30%
101-68-8	4,4'-methylenediphenyl diisocyanate	13 - 30%
3296-90-0	DIBROMONEOPENTYL GLYCOL	1.5 - 5%
26447-40-5	methylenediphenyl diisocyanate	1.5 - 5%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

Most important symptoms and effects, both acute and delayed No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required.

· **Environmental precautions:** No special measures required.

(Contd. on page 4)



Trade name: 39967 Pillar Foam

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	0.15 mg/m ³
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m ³
26447-40-5	methylenediphenyl diisocyanate	29 mg/m ³

· **PAC-2:**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3.6 mg/m ³
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
26447-40-5	methylenediphenyl diisocyanate	40 mg/m ³

· **PAC-3:**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	22 mg/m ³
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
26447-40-5	methylenediphenyl diisocyanate	240 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Thorough dedusting.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

Trade name: 39967 Pillar Foam

(Contd. of page 4)

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m ³ , 0.005 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

According to product specification

· **Odor:**

Characteristic

(Contd. on page 6)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39967 Pillar Foam

(Contd. of page 5)

· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	190 °C
· Flash point:	>93 °C
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	400 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	0.4 Vol %
Upper:	0.0 Vol %
· Vapor pressure:	Not applicable.
· Density at 20 °C:	1.1744 g/cm ³
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	100.0 %
· Other information	No further relevant information available.

* **10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 7)



Trade name: 39967 Pillar Foam

(Contd. of page 6)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

3

101-68-8 4,4'-methylenediphenyl diisocyanate

3

3296-90-0 DIBROMONEOPENTYL GLYCOL

2B

· **NTP (National Toxicology Program)**

3296-90-0 DIBROMONEOPENTYL GLYCOL

R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Generally not hazardous for water

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

USA

(Contd. on page 8)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39967 Pillar Foam

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	
· DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks	NOT REGULATED
· UN "Model Regulation":	Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
None of the ingredient is listed.
· Section 313 (Specific toxic chemical listings):
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues
101-68-8 4,4'-methylenediphenyl diisocyanate
3296-90-0 DIBROMONEOPENTYL GLYCOL
26447-40-5 methylenediphenyl diisocyanate

(Contd. on page 9)

Trade name: 39967 Pillar Foam

(Contd. of page 8)

· **TSCA (Toxic Substances Control Act):**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
101-68-8	4,4'-methylenediphenyl diisocyanate
3296-90-0	DIBROMONEOPENTYL GLYCOL
26447-40-5	methylenediphenyl diisocyanate

· **Proposition 65**

· **Chemicals known to cause cancer:**

3296-90-0	DIBROMONEOPENTYL GLYCOL
-----------	-------------------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CBD
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomeres and homologues

4,4'-methylenediphenyl diisocyanate

Acrylic Polyol

methylenediphenyl diisocyanate

· **Hazard statements**

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 10)

Trade name: 39967 Pillar Foam

(Contd. of page 9)

· Precautionary statements

- P201 *Obtain special instructions before use.*
- P202 *Do not handle until all safety precautions have been read and understood.*
- P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
- P264 *Wash thoroughly after handling.*
- P271 *Use only outdoors or in a well-ventilated area.*
- P272 *Contaminated work clothing must not be allowed out of the workplace.*
- P280 *Wear protective gloves/protective clothing/eye protection/face protection.*
- P284 *[In case of inadequate ventilation] wear respiratory protection.*
- P302+P352 *IF ON SKIN: Wash with plenty of water.*
- P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
- P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P308+P313 *IF exposed or concerned: Get medical advice/attention.*
- P312 *Call a POISON CENTER/doctor if you feel unwell.*
- P314 *Get medical advice/attention if you feel unwell.*
- P321 *Specific treatment (see on this label).*
- P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*
- P337+P313 *If eye irritation persists: Get medical advice/attention.*
- P342+P311 *If experiencing respiratory symptoms: Call a POISON CENTER/doctor.*
- P362+P364 *Take off contaminated clothing and wash it before reuse.*
- P363 *Wash contaminated clothing before reuse.*
- P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
- P405 *Store locked up.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Steve Gaver (sgaver@semproducts.com)

· Date of preparation / last revision 06/28/2017 / 5

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 11)



Printing date 06/28/2017

Reviewed on 06/21/2017

Trade name: 39967 Pillar Foam

(Contd. of page 10)

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
*** Data compared to the previous version altered.**

USA