

## 1 Identification

· **Product identifier**

· **Trade name:** A1500 Series Aerospace Color Coat

· **Article number:**

A15011, A15016, A15081, A15086, A15501, A15506, A15511, A15516, A15521, A15526, A15531, A15536, A15541, A15546, A15561, A15566, A15571, A15576, A15591, A15596, A22222

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225

· **Information department:**

cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Danger

**Trade name: A1500 Series Aerospace Color Coat**

(Contd. of page 1)

· **Hazard-determining components of labeling:**

toluene

butanone

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 3)

**Trade name: A1500 Series Aerospace Color Coat**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

|            |    |                |
|------------|----|----------------|
| HEALTH     | *1 | Health = *1    |
| FIRE       | 3  | Fire = 3       |
| REACTIVITY | 0  | Reactivity = 0 |

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

|           |                                 |           |
|-----------|---------------------------------|-----------|
| 108-88-3  | toluene                         | 70 - 100% |
| 78-93-3   | butanone                        | 7 - 10%   |
| 108-65-6  | 2-methoxy-1-methylethyl acetate | 1.5 - 5%  |
| 2807-30-9 | 2-(propyloxy)ethanol            | 1.5 - 5%  |
| 100-41-4  | ethylbenzene                    | ≤1%       |

**4 First-aid measures**

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

USA

(Contd. on page 4)



**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 3)

## 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### · Protective Action Criteria for Chemicals

#### · PAC-1:

|             |  |          |
|-------------|--|----------|
| 108-88-3    | toluene                                | 67 ppm   |
| 78-93-3     | butanone                               | 200 ppm  |
| 108-65-6    | 2-methoxy-1-methylethyl acetate        | 50 ppm   |
| 2807-30-9   | 2-(propyloxy)ethanol                   | 2.2 ppm  |
| 1330-20-7   | xylene                                 | 130 ppm  |
| 112926-00-8 | precipitated Silica (Silica-Amorphous) | 18 mg/m3 |
| 67-56-1     | methanol                               | 530 ppm  |
| 1333-86-4   | Carbon black                           | 9 mg/m3  |
| 100-41-4    | ethylbenzene                           | 33 ppm   |
| 78-83-1     | butanol                                | 150 ppm  |
| 57-55-6     | Methyl glycol                          | 30 mg/m3 |

#### · PAC-2:

|             |  |             |
|-------------|--|-------------|
| 108-88-3    | toluene                                | 560 ppm     |
| 78-93-3     | butanone                               | 2700* ppm   |
| 108-65-6    | 2-methoxy-1-methylethyl acetate        | 1,000 ppm   |
| 2807-30-9   | 2-(propyloxy)ethanol                   | 24 ppm      |
| 1330-20-7   | xylene                                 | 920* ppm    |
| 112926-00-8 | precipitated Silica (Silica-Amorphous) | 200 mg/m3   |
| 67-56-1     | methanol                               | 2,100 ppm   |
| 1333-86-4   | Carbon black                           | 99 mg/m3    |
| 100-41-4    | ethylbenzene                           | 1100* ppm   |
| 78-83-1     | butanol                                | 1,300 ppm   |
| 57-55-6     | Methyl glycol                          | 1,300 mg/m3 |

#### · PAC-3:

|           |                                 |           |
|-----------|---------------------------------|-----------|
| 108-88-3  | toluene                         | 3700* ppm |
| 78-93-3   | butanone                        | 4000* ppm |
| 108-65-6  | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 2807-30-9 | 2-(propyloxy)ethanol            | 140 ppm   |
| 1330-20-7 | xylene                          | 2500* ppm |

(Contd. on page 5)



**Trade name: A1500 Series Aerospace Color Coat**

|             |  |                         |
|-------------|--|-------------------------|
|             |  | (Contd. of page 4)      |
| 112926-00-8 | precipitated Silica (Silica-Amorphous) | 1,200 mg/m <sup>3</sup> |
| 67-56-1     | methanol                               | 7200* ppm               |
| 1333-86-4   | Carbon black                           | 590 mg/m <sup>3</sup>   |
| 100-41-4    | ethylbenzene                           | 1800* ppm               |
| 78-83-1     | butanol                                | 8000* ppm               |
| 57-55-6     | Methyl glycol                          | 7,900 mg/m <sup>3</sup> |

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 108-88-3 toluene

|     |   |
|-----|---|
| PEL | Long-term value: 200 ppm<br>Ceiling limit value: 300; 500* ppm<br>*10-min peak per 8-hr shift         |
| REL | Short-term value: 560 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 375 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 75 mg/m <sup>3</sup> , 20 ppm<br>BEI   |

### 78-93-3 butanone

|     |   |
|-----|---|
| PEL | Long-term value: 590 mg/m <sup>3</sup> , 200 ppm  |
| REL | Short-term value: 885 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 590 mg/m <sup>3</sup> , 200 ppm |

(Contd. on page 6)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 5)

|   |  |
|---|--|
| TLV   | Short-term value: 885 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 590 mg/m <sup>3</sup> , 200 ppm<br>BEI |
| <b>108-65-6 2-methoxy-1-methylethyl acetate</b> |  |
| WEEL  | Long-term value: 50 ppm  |
| <b>100-41-4 ethylbenzene</b>                    |  |
| PEL   | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm   |
| REL   | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV   | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm<br>BEI  |

· **Ingredients with biological limit values:**

**108-88-3 toluene**

|     |  |
|-----|--|
| BEI | 0.02 mg/L<br>Medium: blood<br>Time: prior to last shift of workweek<br>Parameter: Toluene                      |
|     | 0.03 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Toluene   |
|     | 0.3 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: o-Cresol with hydrolysis (background) |

**78-93-3 butanone**

|     |   |
|-----|---|
| BEI | 2 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: MEK |
|-----|---|

**100-41-4 ethylbenzene**

|     |   |
|-----|---|
| BEI | 0.7 g/g creatinine<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
|     | -<br>Medium: end-exhaled air<br>Time: not critical<br>Parameter: Ethyl benzene (semi-quantitative)  |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 7)

**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 6)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

|                        |                                    |
|------------------------|------------------------------------|
| <b>Form:</b>           | Liquid                             |
| <b>Color:</b>          | According to product specification |
| <b>Odor:</b>           | Characteristic                     |
| <b>Odor threshold:</b> | Not determined.                    |

· **pH-value:** Not determined.

· **Change in condition**

|                                     |               |
|-------------------------------------|---------------|
| <b>Melting point/Melting range:</b> | Undetermined. |
| <b>Boiling point/Boiling range:</b> | 79 °C         |

· **Flash point:** -4 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 514 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

(Contd. on page 8)





Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: A1500 Series Aerospace Color Coat**

(Contd. of page 7)

|   |   |
|---|---|
| · <b>Danger of explosion:</b>                     | <i>In use, may form flammable/explosive vapour-air mixture.</i> |
| · <b>Explosion limits:</b>                        |   |
| <b>Lower:</b>                                     | <i>1.2 Vol %</i>  |
| <b>Upper:</b>                                     | <i>7.0 Vol %</i>  |
| · <b>Vapor pressure at 20 °C:</b>                 | <i>29 hPa</i>   |
| · <b>Density at 20 °C:</b>                        | <i>0.99407 g/cm<sup>3</sup></i>                                 |
| · <b>Relative density</b>                         | <i>Not determined.</i>  |
| · <b>Vapor density</b>                            | <i>Not determined.</i>  |
| · <b>Evaporation rate</b>                         | <i>Not determined.</i>  |
| · <b>Solubility in / Miscibility with Water:</b>  | <i>Not miscible or difficult to mix.</i>                        |
| · <b>Partition coefficient (n-octanol/water):</b> | <i>Not determined.</i>  |
| · <b>Viscosity:</b>                               |   |
| <b>Dynamic:</b>                                   | <i>Not determined.</i>  |
| <b>Kinematic:</b>                                 | <i>Not determined.</i>  |
| · <b>Solvent content:</b>                         |   |
| <b>Organic solvents:</b>                          | <i>84.7 %</i>   |
| <b>VOC content:</b>                               | <i>84.7 %</i>   |
|   | <i>842.3 g/l / 7.03 lb/gal</i>                                  |
| <b>Solids content:</b>                            | <i>15.4 %</i>   |
| · <b>Other information</b>                        | <i>No further relevant information available.</i>               |

\*

## 10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

|   |          |                      |
|---|----------|----------------------|
| · <b>LD/LC50 values that are relevant for classification:</b> |          |                      |
| <b>108-88-3 toluene</b>                                       |          |                      |
| Oral  | LD50     | 5000 mg/kg (rat)     |
| Dermal  | LD50     | 12124 mg/kg (rabbit) |
| Inhalative  | LC50/4 h | 5320 mg/l (mouse)    |

- **Primary irritant effect:**
- **on the skin:** *Irritant to skin and mucous membranes.*
- **on the eye:** *Irritating effect.*

(Contd. on page 9)





Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 8)

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

|           |              |    |
|-----------|--------------|----|
| 108-88-3  | toluene      | 3  |
| 1330-20-7 | xylene       | 3  |
| 1333-86-4 | Carbon black | 2B |
| 100-41-4  | ethylbenzene | 2B |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

|            |                             |
|------------|-----------------------------|
| 68911-87-5 | montmorilontie clay complex |
|------------|-----------------------------|

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN1263

(Contd. on page 10)

Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 9)

· **UN proper shipping name**

· **DOT**

Paint

· **ADR**

1263 Paint, special provision 640D

· **IMDG, IATA**

PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3

· **ADR, IMDG, IATA**



· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**

· **DOT, ADR, IMDG, IATA**

II

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Flammable liquids

· **EMS Number:**

F-E,S-E

· **Stowage Category**

B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **Remarks**

ORM-D 49CFR 173-150,156,306

· **ADR**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: A1500 Series Aerospace Color Coat**

(Contd. of page 10)

· **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

|           |               |
|-----------|---------------|
| 108-88-3  | toluene       |
|           | Acrylic Resin |
| 78-93-3   | butanone      |
| 1330-20-7 | xylene        |
| 67-56-1   | methanol      |
| 100-41-4  | ethylbenzene  |

· **TSCA (Toxic Substances Control Act):**

|            |                                       |
|------------|---------------------------------------|
| 108-88-3   | toluene                               |
| 78-93-3    | butanone                              |
| 51274-00-1 | YELLOW IRON OXIDE                     |
| 108-65-6   | 2-methoxy-1-methylethyl acetate       |
| 2807-30-9  | 2-(propyloxy)ethanol                  |
| 1330-20-7  | xylene                                |
| 67-56-1    | methanol                              |
| 1333-86-4  | Carbon black                          |
| 100-41-4   | ethylbenzene                          |
| 68911-87-5 | montmorilontie clay complex           |
| 61791-55-7 | Amines, N-tallow alkyltrimethylenedi- |
| 78-83-1    | butanol                               |
| 57-55-6    | Methyl glycol                         |
| 7732-18-5  | water                                 |

· **Proposition 65**

· **Chemicals known to cause cancer:**

|           |              |
|-----------|--------------|
| 1330-20-7 | xylene       |
| 1333-86-4 | Carbon black |
| 100-41-4  | ethylbenzene |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

|          |         |
|----------|---------|
| 108-88-3 | toluene |
|----------|---------|

(Contd. on page 12)

**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 11)

|         |          |
|---------|----------|
| 67-56-1 | methanol |
|---------|----------|

· **Cancerogenity categories**

|  |              |    |
|--|--------------|----|
| · <b>EPA (Environmental Protection Agency)</b> |              |    |
| 108-88-3                                       | toluene      | II |
| 78-93-3  | butanone     | I  |
| 1330-20-7                                      | xylene       | I  |
| 100-41-4                                       | ethylbenzene | D  |

· **TLV (Threshold Limit Value established by ACGIH)**

|           |              |    |
|-----------|--------------|----|
| 108-88-3  | toluene      | A4 |
| 1330-20-7 | xylene       | A4 |
| 1333-86-4 | Carbon black | A4 |
| 100-41-4  | ethylbenzene | A3 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

|           |              |
|-----------|--------------|
| 67-56-1   | methanol     |
| 1333-86-4 | Carbon black |

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene  
butanone

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 13)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: AI500 Series Aerospace Color Coat**

(Contd. of page 12)

- P303+P361+P353** *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- P304+P340** *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
- P305+P351+P338** *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P308+P313** *IF exposed or concerned: Get medical advice/attention.*
- P312** *Call a POISON CENTER/doctor if you feel unwell.*
- P314** *Get medical advice/attention if you feel unwell.*
- P321** *Specific treatment (see on this label).*
- P332+P313** *If skin irritation occurs: Get medical advice/attention.*
- P337+P313** *If eye irritation persists: Get medical advice/attention.*
- P362+P364** *Take off contaminated clothing and wash it before reuse.*
- P370+P378** *In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*
- P403+P233** *Store in a well-ventilated place. Keep container tightly closed.*
- P403+P235** *Store in a well-ventilated place. Keep cool.*
- P405** *Store locked up.*
- P501** *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/28/2017 / 6

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

(Contd. on page 14)



Printing date 06/28/2017

Reviewed on 06/21/2017

**Trade name: A1500 Series Aerospace Color Coat**

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. of page 13)

· **\* Data compared to the previous version altered.**

USA