Printing date 09/25/2018

Version number 13

Reviewed on 09/25/2018

1 Identification

- · Product identifier
- · Trade name: 40542, 40549 Carbo-Fill Plus
- · Article number: 40542, 40549
- · Application of the substance / the mixture Filler and surfacer
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: styrene

(Contd. on page 2)

Printing date 09/25/2018 Version number 13



Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 1)

Talc

BISPHENOL A DIGLYCIDAL METHACRYLATE

Glass

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

P201 *Obtain special instructions before use.*

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse. P362+P364 P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. P403+P233

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:			
14807-96-6	Talc	40-60%	
100-42-5	styrene	10-13%	
1565-94-2	BISPHENOL A DIGLYCIDAL METHACRYLATE	10-13%	
65997-17-3	Glass	1-1.5%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

<i>PAC-1:</i>		
100-42-5	styrene	20 ppm
13463-67-7	titanium dioxide	30 mg/m
65997-17-3	Glass	15 mg/m
7440-44-0	carbon fiber	6 mg/m ³
· PAC-2:		
100-42-5	styrene	130 ppm
13463-67-7	titanium dioxide	330 mg/m
65997-17-3	Glass	170 mg/m
7440-44-0	carbon fiber	330 mg/m
- PAC-3:		
100-42-5	styrene	1100* ppm
13463-67-7	titanium dioxide	2,000 mg/m
65997-17-3	Glass	990 mg/m³
7440-44-0	carbon fiber	2,000 mg/m

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 5)

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

100-42-5 styrene

PEL Long-term value: 100 ppm

Ceiling limit value: 200; 600* ppm

*5-min peak in any 3 hrs

REL Short-term value: 425 mg/m³, 100 ppm

Long-term value: 215 mg/m³, 50 ppm

TLV Short-term value: (170) mg/m³, (40) ppm

Long-term value: (85) NIC-8.5 mg/m³, (20) NIC-2 ppm

BEI, NIC-A3, NIC-OTO

· Ingredients with biological limit values:

100-42-5 styrene

BEI 400 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

 $0.2 \, mg/L$

Medium: venous blood Time: end of shift

Parameter: Styrene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 5)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

$\alpha \mathbf{n} \mathbf{n}$		•	properties
U Physica	anac	nomicai	nranarties
		e a se e e a a a a a a a a a a a a a a a	

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 145.2 °C

· Flash point: 32 °C

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 480 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 8.9 Vol %

(Contd. on page 7)

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

		(Contd. of page
· Vapor pressure at 20 °C:	6 hPa	
· Density at 20 °C:	1.57227 g/cm³	
Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/v	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	12.4 %	
VOC content:	12.40 %	
Solids content:	87.6 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
100-42-5 s	tyrene		
Oral	LD50	5,000 mg/kg (rat)	
Inhalative	LC50/4 h	24 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 8)

-USA

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 7)

· Carcinogenic categories

· Carcinogen	ic categories	
· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc	3
100-42-5	styrene	2B
13463-67-7	titanium dioxide	2B
	RHEOLOGICAL ADDITIVE	2A <1% 14808-60-7
· NTP (Natio	nal Toxicology Program)	
100-42-5 styrene		
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

7 4	4.5		 r	7 ·
	Tran	CHOP	orma	tion
		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	 	*****

14 Pransport information				
· UN-Number · DOT, ADR, IMDG, IATA	UN3269			
· UN proper shipping name				
$\cdot DOT$	Polyester resin kit			
· ADR	3269 Polyester resin kit			

(Contd. on page 9)

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 8) POLYESTER RESIN KIT · IMDG, IATA · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: · Special precautions for user Warning: Flammable liquids F-E,S-D· EMS Number: · Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot ADR$ · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: See SP340 · UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

14807-96-6 Talc

(Contd. on page 10)

SEM

Printing date 09/25/2018

Version number 13

Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

	(Contd. of page	9)
100-42-5	styrene	
· TSCA (Toxi	c Substances Control Act):	
14807-96-6	Talc	
100-42-5	styrene	
1565-94-2	BISPHENOL A DIGLYCIDAL METHACRYLATE	
13463-67-7	titanium dioxide	
1317-65-3	GROUND CALCIUM CARBONATE	
65997-17-3	Glass	
	carbon fiber	
· Proposition		
	cnown to cause cancer:	
100-42-5		
13463-67-7	titanium dioxide	
· Chemicals k	nown to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
· Chemicals k	nown to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
Chemicals k	nown to cause developmental toxicity:	
None of the	ingredients is listed.	
· Cancerogen	ity categories	
· EPA (Enviro	onmental Protection Agency)	
None of the	ingredients is listed.	
· TLV (Thresi	hold Limit Value established by ACGIH)	
14807-96-6	Talc A-	4
100-42-5	styrene A-	4
13463-67-7	titanium dioxide A-	4
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS07 GH

- · Signal word Danger
- · Hazard-determining components of labeling:

styrene

Talc

BISPHENOL A DIGLYCIDAL METHACRYLATE

Glass

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

(Contd. on page 11)

SEM

Printing date 09/25/2018 Version number 13 Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 10)

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- Date of preparation / last revision 09/25/2018 / 12
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 12)

SEM

Printing date 09/25/2018

Version number 13

Reviewed on 09/25/2018

Trade name: 40542, 40549 Carbo-Fill Plus

(Contd. of page 11)

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

* Data compared to the previous version altered.

USA