SEM 70100 QUICK SPRAY

Minimal clean up **Excellent** coverage Quick & easy setup Attaches directly to 70039





When used according to directions, **SEM** guarantees to the purchaser that all **DUAL-MIX** products will perform to specifications forever. This warranty covers reasonable costs for labor, loss of use of the vehicle, parts and materials only, and excludes consequential or incidental damages.






70100 QUICK SPRAY

SYSTEM

70100 QUICK SPRAY SYSTEM enables the user to duplicate OEM seam sealer texture while utilizing the 2K technology of **39377 SEAM SEALER**, **39477 BEIGE SEAM SEALER**, **40377 HEAVY BODIED BLACK SEAM SEALER**, **40977 SOUND & SEAL**. **70100** quickly attaches to a **70039 UNIVERSAL PNEUMATIC APPLICATOR** to spray material with a flat or round pattern.

OPERATION

- 1. Attach T-connection to pneumatic dispensing gun.
- 2. Close slide valve.
- 3. Install equalized cartridge with static mixer into pneumatic dispensing gun.
- 4. Lock air manifold with desired air cap onto static mixer.
- 5. Attach PU tubing with quick connect to the air manifold.
- 6. Set air flow of pneumatic dispensing gun to max.
- 7. Open slide valve.
- 8. Dispense test material prior to applying to job to insure uniform color and to avoid marbling.
- 9. Use the air flow adjustment assembly to fine tune the spray.







PART NUMBERS

- **70100 QUICK SPRAY SYSTEM STARTER KIT:** one (1) air manifold, one (1) adapter assembly, one (1) retaining ring, one (1) round air cap, one (1) flat air cap, PU tubing, six (6) static mixers and one (1) nut.
- **70101** ROUND AIR ASSEMBLY: one (1) air manifold, one (1) retaining ring and one (1) round air cap.
- **70102** FLAT AIR ASSEMBLY: one (1) air manifold, one (1) retaining ring and one (1) flat air cap.
- **70103 STATIC MIXERS:** six (6) static mixers and one (1) nut.
- **70104 ADAPTER ASSEMBLY:** T-connection with 1/4" male NPT to accept customer-supplied air connection, slide valve, air flow adjustment assembly and PU tubing.

For more information, see

TECHNICAL DATA SHEET or

visit www.semproducts.com



70100 39377



20477



40377



40977

