

Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

Metal Bite Finishing Glaze is a two-component polyester finishing glaze that quickly fills sand scratches and other minor imperfections.

FEATURES

- Fast drying to a tack-free finish
- · Seals the repair area and prevents staining
- Exceptional sanding and feather edge
- Outstanding adhesion
- Use on aluminum, steel, SMC and fiberglass

SUITABLE SUBSTRATES

- Aluminum
- Steel
- SMC
- Fiberglass

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39592	Metal Bite Finishing Glaze	Lt. Blue	24 oz. Tube
Working time:			3-5 minutes @ 100
grams			
Sand time:			10-15 minutes

Check local VOC regulations to ensure compliance in your area.

HANDLING AND APPLICATION

PREPARATION:

- **1.** Clean area with **SEM Solve** or **XXX Universal Surface Cleaner**. The surface must be free of dirt, oil, grease and rust.
- 2. Sand area to be filled with 80-180 grit paper.
- 3. Blow off and re-clean with SEM Solve or XXX Universal Surface Cleaner.

MIXING:

1. Knead container well before dispensing.

- **2.** Mix a ribbon of cream hardener with a golf ball sized quantity of **Metal Bite Finishing Glaze**.
- 3. Stir the mixture until a uniform color is achieved. Mix no more than can be used in 3 minutes.

APPLICATION:

- **1.** Apply the putty to the repair area using a spreader. The film build should not exceed 1/8 inch.
- 2. Allow the area to cure for approximately 10-15 minutes and then sand with 180 grit paper.
- **3.** Refer to the paint manufacturer's instructions to complete the repair.

STORAGE:

Metal Bite Finishing Glaze should be stored between 40-80°F (4-27°C). The shelf life of **Metal Bite Finishing Glaze** is 2 years when stored under normal conditions.

RELATED PRODUCTS

Part:	Product Name:	Size:
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.